

DATASHEET

CA146LED / CA148LED
 CA146IU / CA148IU
 Canterbury Intelligent Dimmer
www.thrion.co.uk



| FINISH | Brushed Chrome | | Matt Black | | Black Nickel | | Brushed Chrome | | Black Nickel | | |
|--|--|---------------|---------------|---------------|---------------|---------------|-------------------------|--------------------|---------------|---------------|--|
| | CA146LED BC | CA148LED BC | CA146LED MB | CA148LED MB | CA146LED BN | CA148LED BN | CA146IU BC | CA148IU BC | CA146IU BC | CA148IU BC | |
| PART CODE | 1Gang 2Way | 2Gang 2Way | 1Gang 2Way | 2Gang 2Way | 1Gang 2Way | 2Gang 2Way | 1Gang 2Way | 2Gang 2Way | 1Gang 2Way | 2Gang 2Way | |
| DESCRIPTION | | | | | | | | | | | |
| GLS | 150W | | | | | | 200W | | | | |
| Mains Halogen | 120W | | | | | | 150W | | | | |
| Low Voltage Halogen (Max. 10 transformers per gang) | 120W | | | | | | 150W | | | | |
| Eco Halogen | 120W | | | | | | 150W | | | | |
| Dimmable LED | 1 to 10 LEDs(max. 100W) | | | | | | 1 to 10 LEDs(max. 120W) | | | | |
| Dimmable CFL | 100W | | | | | | 120W | | | | |
| MINIMUM MOUNTING DEPTH (MM) | 35 | | | | | | | | | | |
| DIMENSIONS (MM) | Height: 86 | | | | Width: 86 | | | Plate Thickness: 7 | | | |
| INPUT VOLTAGE | Mains 250V a.c. | | | | | | | | | | |
| TERMINAL CAPACITY | 3 x 1.5mm ² or 1 x 2.5mm ² | | | | | | | | | | |
| IP RATING | IP 20 | | | | | | | | | | |
| WARRANTY | 5 years | | | | | | | | | | |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes | | | | | | | | | | |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60669-2-1 | | | | | | | | | | |