

DATASHEET

CA146LED / CA148LED
 CA146IU / CA148IU
 Canterbury Intelligent Dimmer
www.thrion.co.uk



FINISH	Brushed Chrome		Matt Black		Black Nickel		Brushed Chrome		Black Nickel		
	CA146LED BC	CA148LED BC	CA146LED MB	CA148LED MB	CA146LED BN	CA148LED BN	CA146IU BC	CA148IU BC	CA146IU BC	CA148IU BC	
DESCRIPTION	1Gang 2Way	2Gang 2Way	1Gang 2Way	2Gang 2Way	1Gang 2Way	2Gang 2Way	1Gang 2Way	2Gang 2Way	1Gang 2Way	2Gang 2Way	
GLS	150W						200W				
Mains Halogen	120W						150W				
Low Voltage Halogen (Max. 10 transformers per gang)	120W						150W				
Eco Halogen	120W						150W				
Dimmable LED	1 to 10 LEDs(max. 100W)						1 to 10 LEDs(max. 120W)				
Dimmable CFL	100W						120W				
MINIMUM MOUNTING DEPTH (MM)	35										
DIMENSIONS (MM)	Height: 86				Width: 86			Plate Thickness: 7			
INPUT VOLTAGE	Mains 250V a.c.										
TERMINAL CAPACITY	3 x 1.5mm ² or 1 x 2.5mm ²										
IP RATING	IP 20										
WARRANTY	5 years										
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes										
MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-2-1										