

DATASHEET



VN 050/VN 053/VN 056 /VN 056M /VN056N

VN 059/VN 059M/VN059N

White 13A Fused Connection Unit

www.thrion.co.uk



PART CODE	VN050	VN053	VN056	VN056M	VN056N	VN059	VN059M	VN059N
DESCRIPTION	13A Fused Connection Unit+Neon	13A Fused Connection Unit	13A Switched Fused Connection Unit+Neon	13A Switched Fused Connection Unit+Neon Bottom Flex Outlet	13A Switched Fused Connection Unit+Neon Front Flex Outlet	13A Switched Fused Connection Unit	13A Switched Fused Connection Unit Bottom Flex Outlet	13A Switched Fused Connection Unit Front Flex Outlet
FINISH	White							
MINIMUM MOUNTING DEPTH (MM)	25							
DIMENSIONS (MM)	Height: 86		Width: 86			Plate Thickness: 10		
INPUT VOLTAGE	Mains 250V a.c.							
MAXIMUM LOAD (A)	13							
TERMINAL CAPACITY	3 x 2.5mm ² or 3 x 4mm ² or 1 x 6mm ²							
IP RATING	IP 20							
WARRANTY	25 years							
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes							
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4							