

120AH 24V DEEP CYCLE LFP BATTERY

DCS-24V-120AH



ELECTRICAL SPECIFICATIONS	
Nominal Voltage	25.6V
Nominal Capacity	120Ah
Self Discharge (Storage)	≤ 3% per Month
Parallel Connection	Max 10
Series Connection	No
CHARGE SPECIFICATIONS @ +77F (± 5F)	
Maximum Continuous Charge Current	≤ 120A (1.0C)
Recommend Charge Current	≤ 80A (0.7C)
Alternator/DC Charger Current Limit	≤ 80A
Cycling Voltage	23.0 - 29.2V
Charge Voltage	28.6 - 29.2V
Float Voltage	27.0V
DISCHARGE SPECIFICATIONS @ +77F (± 5F)	
Maximum Continuous Discharge Current	≤ 150A (1.25C)
Lithium Cranking Amps (LCA)	1000 LCA
Recommended Low Voltage Disconnect	24.0V
Discharge Under-Voltage Protection	23.0V
CHEMISTRY SPECIFICATIONS	
Cell Type	Cylindrical Cells - 3.2V (15Ah)
Cell Chemistry	Lithium Ferro Phosphate Cells (LFP)
Cell C-Rate	2C
Cycle Performance	4000 Cycles @ 100% DOD*
*4000 Cycles @ 100% DOD ≤ 80% Capacity Retention @ 77F	
WARRANTY	
Warranty Period	3 Years

PHYSICAL SPECIFICATIONS	
Enclosure Material	ABS Plastic
Dimensions (L x W x H)	20.472" x 9.370" x 8.543"
Weight	54 lbs
Terminal Type	Top Mount Steel/Copper M8 x 1.25
Terminal Configuration	LHP or RHP
Terminal Torque	9 ft-lbs (12 Nm)
Ingress Protection	IP54
BMS SPECIFICATIONS	
BMS Type	DCS 3S
BMS Low Voltage Cut Off (LVC)	23.0V
BMS High Voltage Cut Off (HVC)	29.6V
Cell Balancing Type	Active Cell Balancing
Data Communication	Bluetooth
TEMPERATURE SPECIFICATIONS	
Charge Temperature Range	+25°F to +149°F
Discharge Temperature Range	-13°F to +176°F
BMS High Temperature Cut-Off	230°F
BMS Reconnect Temperature	176°F
HEATING ELEMENT SPECIFICATIONS	
Heater Activation Temperature	N/A
Heater Shut Off Temperature	N/A
Energy Consumption	N/A
COMPLIANCE SPECIFICATIONS	
Certifications	CE, UL 1642, IEC 62133 & 62619
BMS Certification	MIL-STD-810G (Method 514.6)
Shipping Classification	UN 38.3