

Filter Replacement

Do you prefer video
Instruction ?

Scan Code for a brief
video on how to replace
the filters



Instruction for KYK Genesis, EOS Revelation I&II

1. Turn the machine off
2. Open the filter cover and unhook the wire connected to the filter sensor on top of the filter.
3. Hold the top of the filter and turn it to the left, then pull out. (in case filter does not turn easily: the rubber seal on bottom of the filter sticks due to sitting in that position for some time. In case this happens, there are **2 options**:
 - a. Get some help and then turn the filter to left with **four** hands)
 - b. Alternatively get a 'boa constrictor' in a plumbing outlet, which is a tool that acts as a spanner to open the filter cartridges.
4. Remove the stickers covering the inlet and outlet of new filter
5. Insert the filter bottom side first, push in, then turn to the right as marked on the top of new filter
6. Connect the electric wire to the filter monitoring sensor
7. Close the filter cover.
8. Turn the machine on and touch the activation sensor (on/off)

Clean the machine for 20 seconds, 20 seconds later, touch the sensor for Alkaline water. Let the water run through new filters for 2 - 3 minutes, 3 minutes later, it is ready to drink.

The filter counter automatically goes to 6000 l/9000
l KYK25000 and 4000/8000 litres EOS Platinum



**Do you prefer video
Instruction ?**

Scan Code for a brief
video on how to replace
the filters



EOS Revelation I & II Filter Reset

Press alkaline and pure button simultaneously for 5 seconds. Then loudspeaker will flash which shows that you are in the computer menu

- 2) Make sure that the display shows pH 9 to begin with.
- 3) Press acidic once, again, and again until it shows 'off' and the filter life of F1 flashing.
- 4) PRESS button ALKALINE once to set it to ON. Then press and hold ACIDIC to set the filter 1 . It should now show all bars again.
- 4) If more filters need to be reset, then press acidic again to go to the next level, showing filter 2 flashing and OFF.
- 5) Press alkaline once to set it to ON, and then hold ACIDIC for a few seconds to set filter 2 to all bars. That should reset the filter life.
- 6) Then turn ionizer on: ON button and let the new filters flush, until the menu goes to normal functioning.

Please note: After each dispensing of ionized water, the ionizer will turn itself on for an automatic cleaning cycle for approx 15 seconds. This is normal and needs to happen to recognition electrolytic plates

Re reprogramming of ionizer, or resetting the filter counters:

When you want to set the new selection it says in manual (Page 27)

When you make any adjustment to an option in the mode you must hit "Acidic (set)" to save the changes you made. It needs to say: Hold the button 'Acidic (Set)' for about 5 seconds to save the new setting.

