CONCRETE FORMS



High Density Overlay (HDO)

PANEL TYPE	2' x 8' 2' x 9' 2' x 10' 2' x 12'	4' x 8' 4' x 9' 4' x 10' 4' x 12'		
HDO				

AVAILABLE IN 3/8" | 1/2" | 5/8" | 11/16" | 3/4" | 1" | 1-1/8"

JUMBO DOUGLAS FIR CONCRETE FORM PANELS

- Grade Stamped with the APA and PS-1 Trademarks
- Durable Factory Edge Seal
- o Standard Class 1 Concrete Forming Designation
- o Struc 1 Panel Construction Available

HIGH QUALITY CONCRETE FINISH FORMING PANELS.

LONG Direction Across Supports - Plywood Continuous Across Two or More Spans

	PLYWOOD THICKNESS - ALLOWABLE PRESSURE (PSF)								
SUPPORT	1/2"		5/8″		3/4"		1-1/8″		
SPACING	1/360	1/270	1/360	1/270	1/360	1/270	1/360	1/270	
8″	1,155	1,155	1,365	1,365	2,040	2,040	2,949	2,949	
12″	490	515	705	845	995	995	1,826	1,826	
16″	210	280	320	395	495	560	1,157	1,199	
19.2″	120	160	190	255	300	390	755	832	
24″	-	-	100	130	160	215	432	533	

SHORT Direction Across Supports - Plywood Continuous Across Two or More Spans

	PLYWOOD THICKNESS - ALLOWABLE PRESSURE (PSF)								
SUPPORT	1/2″		5/8"		3/4"		1-1/8"		
SPACING	1/360	1/270	1/360	1/270	1/360	1/270	1/360	1/270	
8″	485	555	775	775	1,690	1,690	2,586	2,501	
12″	140	185	355	410	715	815	1,601	1,601	
16″	-	-	150	200	310	415	957	1,028	
19.2″	-	-	105	130	225	255	571	571	
24″	-	-	-	-	115	155	365	365	

Panels are available with either one or two good sides. The hard, largely opaque surface of the high density overlay surface of the thermosetting phenolic resin impregnated material allows for a nearly polished concrete finish, largely masking any wood telegraphing through the overlay.

Panels are edge sealed at the mill, however no surface release coating is applied.

All our concrete form panels are manufactured in Harrisburg, Oregon by Eagle Plywood Specialties and subject to 3rd party quality programs administered by APA – The Engineered Wood Association

GreenwoodProducts.com

 ${\tt Salesteam} @ {\tt GreenwoodProducts.com} \\$

ENHANCE JOB-SITE EFFICIENCIES AND REDUCE COSTS WITH OVERSIZE PANELS

800-333-3898