

PlyDek



LONG LASTING TOP QUALITY STRUCTURAL PANEL

- Available either good 1 or 2-sided solid face and back
- No open defect allowed in on faces or back as specified
- 100% fir (face-core-back) available in structural specification
- Pressure preserved in accordance with AWP Ground Contact standards or untreated

Why Use PlyDek?

PlyDek is an enhanced solid laminated general purpose panel to be used in place of low grade panels when quality and long lasting performance are important. Preservative or flame retardant treatments available.

Specifications

SIZES: Standard thicknesses 1/4" through 1" in full 4' x 8' through 5' x 10' sheets. Also available by special order in most widths and lengths up to, and including, 8' wide by 50' long.

GLUE BOND: Marine-type high solid content exterior glue.

SURFACE: Tight-knot solid face allowing no open defects. Fully sanded for receiving carpet or other resilient floor coverings.

MOISTURE CONTENT: Kiln dried after treating in a controlled low temperature environment to assure uniform stability and flatness.

TYPES: Square edge or tongue and groove – 2 edges.

ESTIMATED SHIPPING WEIGHTS: 4' x 8' sheets

1/4" 22 lbs per sheet	1/2" 40 lbs per sheet	3/4" 60 lbs per sheet
5/8" 29 lbs per sheet	5/8" 50 lbs per sheet	1" 77 lbs per sheet


What is PlyDek?


It's an extended life structural panel used in a variety of applications where one or two solid and sanded faces are required. PlyDek can be pressure-preserved impregnated with an eco-friendly preservative designed to resist fungal decay and protect against insect manifestation. PlyDek is also available with a Fire-Retardant Treatment.

Packaging

Three straps with stickers and metal corner protectors.

 GreenwoodProducts.com

 Salesteam@GreenwoodProducts.com

 800-333-3898



LIMITED LIFETIME WARRANTY AVAILABLE

See written warranty for complete details