

Note:

- 1.The installation instructions may differ slightly from the actual operation. If there are any differences,please follow the actual situation or contact us.
- 2.Warning: Please do not disassemble any part by yourself,any improper operation will not be covered by our warranty.



tutorial video

Aftersale Contact:

phone/whatsapp : +86 130 4421 9654

Email: support@hansshow.com

Working Hours (UTC+8):

9:00AM - 18:30PM (Monday to Sunday)

Please leave a message at other times

Note: if the temperature is too cold, please heat adhesive tape with the hairdryer before pasting

Front Row Installation Steps



1.Clean the installation position



2.Tear off the adhesive tape



3.Apply adhesive aid



4.Align the installation position and press the door to stick it



3. Put the large black rubber gasket to the small black rubber gasket (Note: The surface is upward)



4. Tear off the film of the magnet and put the magnet on the rubber ring (the adhesive surface is upward)



5. Close the door and the large black rubber with magnet will stick to the door



6. magnet stick on the door



7. Tear off the plastic film



8. Finish installation

Rear Door Sill Installation Steps



1. Align the installation position



2. Put the positioning sticker on the corresponding position

The subsequent installation steps is the same as before



Note: If the front door sill does not light up after the battery is added, try to reverse the positive and negative poles of the left and right batteries

battery position for front door sill

Battery Replacement



The positive and negative poles of the battery on both sides of the door sill are opposite.