

# SPECIFICATIONS

## BBX-F1200

### RMS Continuous Power (at 14.4 V, 20 - 20kHz)

- Per channel into 4 ohms ( $\leq 1\%$  THD+N) ..... 50 W x 4
- Per channel into 2 ohms ( $\leq 1\%$  THD+N) ..... 70 W x 4
- Bridged 4 ohms ( $\leq 1\%$  THD+N) ..... 130 W x 2

Total MAX Power ..... 1200 W

### S/N Ratio

- IHF A Weighted, Reference: rated power into 4 ohms ..... > 95 dBA

### Input Impedance

- RCA IN ..... 20k ohms

### Frequency Response (+0, -3dB)

..... 5Hz - 50kHz

### Crossover Frequency

- 1/2ch ..... 50 Hz - 500 Hz (-12dB/oct.)
- 3/4ch ..... 50 Hz - 500 Hz (-12dB/oct.)

Input Sensitivity (RCA IN) ..... 0.2 - 8 V

BASS EQ ..... 45Hz, 0dB to +12dB

### Dimensions

- Length ..... 280 (330) mm
- Width ..... 240 mm
- Height ..... 52 mm

Weight ..... 2.7 kg

### NOTE:

For product improvement, specifications and design are subject to change without notice.