

## Description

Vintro No Seal Chalk Paint is our revolutionary furniture paint that can be used indoors or outdoors and doesn't require waxing or lacquering. It is a water based, non-drip, low VOC, multipurpose decorative paint. It can be used on a variety of surfaces and substrates, including wood, metal, masonry and fabric, with minimal preparation. It is incredibly durable once cured and fully washable. It is ideal if you want a smooth, brush-stroke free finish, want to complete a project quickly, or want to use it outdoors.

Vintro Chalk Paint is EN71-3 Certified – also known as 'toy paint regulation safe'. This means that Vintro No Seal Chalk Paint is completely safe for children's rooms and furniture.

## Surface Preparation

Remove any loose flakes of paint or varnish and give your project a good clean with a mild, soapy solution to remove any dust or possible contamination, allow to thoroughly dry. If you are unsure of the history of the piece of furniture, give it a wipe over with a water based clear spirit, which will remove any grease or silicon from spray polishes.

For a smooth finish ensure that any knocks and dents are filled with wood filler, smoothing any uneven areas with a medium grit sandpaper prior to painting and wiping away any dust.

Surfaces with high sheen, gloss, melamine or laminate surfaces should be lightly sanded and wiped clean to help adhesion of paint or a base coat of Vintro Primer should be applied. Previously waxed surfaces should be wiped over with a clean spirit prior to painting.

Unfinished wooden surfaces or stone will only need a clean with mild, soapy solution to ensure it is clean and allow to dry.

## Applying Paint

Open tin and stir thoroughly. Using a good quality synthetic brush, apply paint in a thin even coat in one direction. Leave to dry and repeat if needed.

## Sizes

Available in 200ml and 1 litre tins

## Coverage

A 1 litre tin will cover approx. 19.5m<sup>2</sup> – depending on the properties of the surface, the colour being used and how thickly it is applied.

## Colour

Available in 82 different colours.

## Thinner

In most cases the product does not require thinning prior to use.

## Drying times

Depending on room temperature and relative humidity, the product will normally be touch dry after 30 - 60 minutes. The surface can be recoated after 2 hours. The paint will take 24 hours at 20°C to cure and it is advised

doors and drawers are closed gently until full cure has taken place.

## Uses

Decorating furniture, glassware, metals, plastics, fabrics, leather, brick, stone.

## Technical properties

The product is easy and fast to apply, including overhead, as it is virtually non-drip. It has excellent adhesion properties, dries quickly and is exceptionally low VOC.

## Biological properties

Vintro No Seal Chalk Paint is a non-toxic, non-hazardous, eco-friendly product manufactured in an ecologically responsible way. Thanks to its composition it is virtually innocuous for people and environment. Vintro paints fall into the lowest possible eco-rating, so you don't need to worry about respiratory issues or smell as the products are virtually odourless.

## Storage

Store containers tightly sealed in a cool but frost-free place. Shelf life: 12

months in original sealed container from date of delivery.

## Health & Safety

Keep coating materials, even if non-poisonous, out of the reach of children.

Always read the information on the tin before use. Ensure maximum ventilation during application and drying. Consult product material safety data sheet for further details.

## VOC Directive

EU limit value for this product: (cat A/a): 30g/l (2010) This product contains max. 30g/l VOC tinted.

## Local Manufacturing

All our paints are manufactured in our facility in the UK. We actively source suppliers who produce in an ecologically sustainable and environmentally responsible manner. We source raw materials from local suppliers wherever possible. We are committed to sustainable manufacturing, minimising pollution and minimising our energy and water consumption.

**Disclaimer** - Information contained on this Information Sheet is for guidance only. Advice is given in good faith and to the best of our knowledge but as application process, substrate quality and site conditions are outside of our control, figures stated may vary and no liability can be accepted on the basis of the information supplied. Always read relevant Information Sheets and SDS Sheets prior to use and test in a small area first or contact Vintro prior to use.