



MULTI *Paint* SURFACE

Paint+Primer
— IN ONE —

INSTRUCTIONS

CIONIA MULTI SURFACE PAINT

CIONIA Multi Surface Paint: Your All-in-One Painting Solution

Experience the power of CIONIA Multi Surface Paint, a versatile acrylic brush-on paint designed to make your painting projects easier and more efficient. With its exceptional features, this paint is a game-changer for both beginners and experienced painters.

TIP: In order to prevent leakage and can expansion during transportation, we will reserve some space for the can.

We promise that the weight of the product is sufficient, if you receive the package please check the safety pull ring is intact at the first time. Please contact the platform customer service at the first time if the can leaks, we will contact you at the first time.



CHAT WITH US!

■ Professional team service

We have more than 20 years of experience in production team and customer service team, we have served tens of thousands of customers, so if you have any questions, please feel free to contact us through the purchase platform, we will reply to you within 24 hours.

WHAT YOU NEED TO KNOW BEFORE PAINTING

Multiple Surfaces

Our paint is your go-to choice for a wide range of surfaces, from wood and metal to wicker, plastic/ceramic, wrought iron, and drywall. Versatility is at your fingertips.

Application Conditions

Take note of the ideal application conditions for the paint. Generally, it is best to paint when the temperature is between **40-104°F (5-40°C)**, and the humidity is moderate. Avoid painting in extreme temperatures or high humidity, as it can affect the paint's performance and drying time.

Surface Preparation

Proper surface preparation is crucial for achieving a smooth and long-lasting finish. Make sure the surface is clean, dry, and free from dust, dirt, grease, and any previous coatings. Remove loose or peeling paint using sandpaper or a suitable paint stripper if necessary.

Primer

According to the surface smoothness of the substrate and the paint's specific instructions, using a primer may be recommended when you plan to paint on the log. Priming helps improve adhesion, enhances paint durability, and ensures even color coverage, it also can prevent wood bleeding.

Test Patch

It's a good practice to perform a test patch in an inconspicuous area before painting the entire surface. This allows you to assess the paint's compatibility, coverage, and drying time on your specific type and surface conditions.

Multiple Coats

In most cases, applying 2-3 coats of paint is necessary to achieve the desired color depth and coverage. We recommend you apply 2-3 when using dark color paint and 3-4 coats for light color, allowing 2H between each coat.

Drying Time

The paint to dry completely after 24H before subjecting the painted surface to light use or exposure. After 7 days, heavy use is allowed. Premature contact or exposure to moisture may affect the finish and durability of the paint.

Clean-Up

Properly dispose of any waste materials, such as paint cans, brushes, and cleaning agents, in accordance with local regulations. Clean brushes, rollers, and other tools promptly after use to maintain their performance and extend their lifespan.

Preparing the surface properly before painting is crucial for achieving a smooth and professional-looking finish. Follow these steps for effective surface preparation

1. Clean the Surface: Remove any dirt, dust, or debris from the wood surface using a broom, brush, or vacuum cleaner. For more stubborn dirt or stains, consider using a mild detergent mixed with water and a soft brush to scrub the surface gently. Rinse thoroughly and allow the wood to dry completely before proceeding.



2. Remove Loose or Peeling Paint: If there is any existing paint that is loose, flaking, or peeling, it's important to remove it to ensure good adhesion of the new paint. Use a scraper or sandpaper to gently scrape or sand away the loose paint until you reach a firm, stable surface. Wipe away any debris with a clean cloth.



3. Smooth Rough Areas: Sand any rough or uneven areas of the surface using sandpaper or a sanding block. This helps create a smooth and uniform surface for the paint to adhere to. Start with a coarse-grit sandpaper to remove imperfections, and then switch to a finer-grit sandpaper for a smoother finish. Remove sanding dust with a cloth or vacuum cleaner.



4. Fill Cracks and Holes: Inspect the wood surface for any cracks, holes, or gaps. Use a suitable wood filler or putty to fill these imperfections. Apply the filler according to the manufacturer's instructions, smoothing it out with a putty knife or a spatula. Allow the filler to dry completely, and then sand it lightly to achieve a flush surface.



5. Clean the Surface Again: After sanding and filling, clean the surface once more to remove any residual dust or debris. Use a tack cloth or a slightly damp cloth to wipe the surface thoroughly. Ensure the surface is completely dry before proceeding with the painting process.



By following these preparation steps, you'll create an ideal foundation for the application of our Multi Surface Paint. This ensures better adhesion, a smoother finish, and improved longevity for your painted surfaces.

APPLICATION

When applying our Multi Surface Paint, follow these step-by-step instructions to achieve the best results:

1. Stir the Paint: Before starting, thoroughly stir the paint using a stir stick or paint mixer. This ensures proper mixing of pigments and any settled components for consistent color and performance.



2. Test Application: Perform a small test application on a discreet area of the surface or a test board to ensure color accuracy and desired results. This allows you to make any adjustments or modifications before painting the entire surface.



3. Begin Application: Start painting from the top or one end of the surface and work your way down or across. Use a brush, roller, or sprayer, depending on your preference and the size of the surface. Follow the recommended application method specified in the tool part.



4. Apply an Even Coat: Apply the paint in thin, even coats to achieve a smooth and uniform finish. Avoid excessive paint buildup or heavy application, as it may result in drips, runs, or uneven drying. Maintain a consistent pressure and stroke direction throughout the application process.



5. Overlap Strokes: For consistent coverage, overlap each stroke slightly with the previous one. This technique helps eliminate any gaps or missed spots, ensuring an even distribution of paint.



6. Follow Drying Time: Allow the first coat to dry according to the recommended drying time specified on the product instruction. This time may vary depending on factors such as temperature, humidity, and the type of surface. Avoid touching or disturbing the painted surface during this drying period.



7. Apply Additional Coats: If necessary, apply additional coats of paint to achieve the desired color depth and coverage. Allow each coat to dry completely before applying the next.



8. Maintain Consistency: While applying multiple coats, maintain a consistent technique and stroke direction to achieve a professional finish. Pay attention to any drips, runs, or pooling of paint, smoothing them out or removing them promptly.



9. Allow Final Drying and Curing: After applying the final coat, allow the paint to dry and cure completely before subjecting the surface to heavy use or exposure. This curing process helps the paint fully bond and harden, ensuring its durability and longevity.



10. Clean-Up: Clean brushes, rollers, sprayers, and other application tools promptly after use. Follow the manufacturer's instructions for proper cleaning methods and recommended solvents or cleaning agents. Dispose of any waste materials in accordance with local regulations.



⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Following these application guidelines will help you achieve a professional-looking finish with our Multi Surface Paint. Remember to adhere to the specific instructions provided by the paint manufacturer, as drying times, application techniques, and other recommendations may vary based on the product formulation.

CLEAN-UP

1. CLEANING BRUSHES, ROLLERS OR SPRAY GUNS

Clean your brushes, rollers, or spray guns thoroughly with water or the recommended solvent immediately after use. Do not let the paint dry on the brush or roller, as this will make it difficult to clean.

2. DISPOSING OF UNUSED PAINT

Dispose of any unused paint and empty cans according to local regulations. Do not pour paint down the drain or dispose of it in the trash, as this can be harmful to the environment.

3. STORING PAINT

Store any leftover paint in a cool, dry place. Make sure the lid is tightly sealed to prevent air from entering the can, which can cause the paint to dry out. Always keep paint out of reach of children and pets.

By following these clean-up steps, you'll ensure that your brushes, rollers, or spray guns are kept in good condition, and that any unused paint is disposed of responsibly. This will help you to prolong the life of your tools, and minimize your impact on the environment.



MAINTENANCE

To maintain the longevity and appearance of your surface after painting with our Multi Surface Paint, follow these maintenance tips:



1. CLEANING

Periodically clean the painted surface to remove dirt, debris, and any stains that may accumulate over time. Use a mild detergent or a specialized cleaner recommended by the paint manufacturer. Gently scrub the surface with a soft brush or sponge, and rinse thoroughly with water. Avoid using abrasive cleaners or harsh chemicals that can damage the paint.



2. INSPECT FOR DAMAGE

Regularly inspect the painted surface for any signs of wear, chipping, or peeling. If you notice any areas where the paint has deteriorated or been damaged, address them promptly to prevent further deterioration. Touch up these areas by sanding, priming (if necessary), and applying a fresh coat of paint following the original application instructions.



3. AVOID SCRATCHES AND IMPACT

Be mindful of sharp or rough objects that may scratch or dent the painted surface. Take precautions when moving furniture or other heavy objects to prevent accidental damage. Consider using protective pads or felt under furniture legs to minimize scratching.



4. PROTECT FROM HARSH ELEMENTS

Protect the painted surface from extreme weather conditions, such as prolonged exposure to direct sunlight, rain, or snow. Consider using appropriate protective coverings, such as awnings, shades, or waterproof tarps, to shield the surface when not in use.



5. REAPPLY AS NEEDED

Over time, the painted surface may experience gradual wear and fading due to weather exposure. If you notice significant color fading or diminished protection, consider reapplying a fresh coat of our Multi Surface Paint according to the recommended maintenance schedule provided by the manufacturer. This will help maintain the appearance and protective properties of the paint.



6. AVOID HARSH CLEANING METHODS

When cleaning the painted surface, avoid using abrasive scrub brushes, steel wool, or harsh chemicals. These can strip away the paint. Opt for gentle cleaning methods and mild detergents to preserve the integrity of the paint.

By following these maintenance practices, you can keep your painted surface in optimal condition, extending its longevity and preserving its aesthetic appeal. Regular care and attention will help ensure that the painted surface retains its beauty and protection for years to come.

SAFETY

To maintain the longevity and appearance of your surface after painting with our Multi Surface Paint, follow these maintenance tips:

- 1. Ventilation:** Always work in a well-ventilated area or outdoors to ensure proper air circulation. Open windows and doors to facilitate fresh air flow, especially when painting indoors. This helps minimize exposure to potentially harmful fumes.
- 2. Personal Protective Equipment (PPE):** Wear appropriate personal protective equipment to protect yourself during painting. This may include gloves, safety goggles or glasses, and a dust mask or respirator. our paint is water-based paint, it is low VOC and low odor, so a pair of gloves should be ok.
- 3. Skin Protection:** Avoid direct contact with the paint on your skin. Wear long sleeves, long pants, and closed-toe shoes to protect your skin from accidental splashes or spills. If the paint comes into contact with your skin, wash it off immediately with soap and water.
- 4. Hazardous Materials:** Handle all paint materials, solvents, and cleaning agents with care. Follow the manufacturer's instructions for proper use, storage, and disposal of these materials. Keep them out of reach of children and pets.
- 5. Proper Use of Tools:** Use painting tools, such as brushes, rollers, or sprayers, according to their intended purpose. Follow the manufacturer's instructions for safe and correct tool usage. Clean tools thoroughly after use and store them in a secure location.
- 6. Safe Disposal:** Dispose of paint waste, empty paint cans, and other related materials in accordance with local regulations. Do not pour paint or cleaning agents down drains or dispose of them in household trash unless permitted.
- 7. Read the Product Label:** Carefully read and follow all instructions and warnings provided on the product label. The label contains important safety information specific to the paint product you are using.

By prioritizing safety measures and adhering to these guidelines, you can ensure a safer painting experience and reduce potential risks or accidents associated with using our Multi Surface Paint.

WARNING!

- 1. Do not take it internally.**
- 2. Avoid contact with eyes and skin.**
- 3. Use with adequate ventilation**
- 4. KEEP OUT OF REACH OF CHILDREN.**
- 5. If you experience eye watering, headache, or dizziness, leave the area to obtain fresh air, if continually difficulty is experienced, seek medical attention immediately**



TROUBLESHOOTING

Problem: Paint is not adhering properly to the surface.

Solution: Make sure the surface is clean and free of grease, rust, and other contaminants. If necessary, use a degreaser or sandpaper to prepare the surface before painting. Follow the preparation steps outlined in the Preparation section of this manual.

Problem: Paint is peeling or cracking.

Solution: This may be due to a surface that was not properly prepared, or due to moisture or humidity. Make sure the surface is dry before painting, and avoid painting in high humidity conditions. Sand down any areas of peeling or cracking and reapply the paint.

Problem: Paint is bubbling.

Solution: This may be due to moisture or contamination on the surface. Sand down any areas of bubbling and reapply the paint. Make sure the surface is completely dry before painting.

Problem: Paint is too thin or too thick.

Solution: If the paint is too thin, it may be due to over-thinning with water. If it's too thick, it may be due to improper mixing or application. If you find that the paint is too thick or if you need to use a spray gun, the recommended dilution ratio is less than 5%.

If you experience any other issues with the paint, consult the label or contact the manufacturer for further assistance.

FAQ

Q How long does the Multi Surface Paint take to dry?

A The drying time of our Multi Surface Paint can vary depending on factors such as temperature, humidity, and the thickness of the paint application. Typically, the paint will dry to the touch within 2 hours, but it is recommended to allow a full 24 hours or more for the paint to cure and harden before subjecting it to heavy use or exposure.

Q Can I paint over an existing layer of paint with the Multi Surface Paint?

A Yes, in most cases, you can paint over an existing layer of paint with our Multi Surface Paint. However, it is important to ensure that the existing paint is in good condition, properly adhered to the surface, and free from any loose or flaking areas. Lightly sand the surface and clean it before applying the new paint. If there are any areas of concern, it is advisable to consult the manufacturer for specific guidance on painting over existing paint.

Q How long will the painted surface last before it needs to be repainted?

A The longevity of the painted surface will depend on various factors such as weather exposure, maintenance, and the quality of the paint application. With proper surface preparation, application, and regular maintenance, our Paint can provide durable protection and lasting color for several years. However, it is recommended to monitor the condition of the painted surface and consider repainting when signs of wear, fading, or damage become noticeable.

For any additional questions or specific inquiries about our Multi Surface Paint, we encourage you to consult the product label or reach out to the manufacturer directly. They will provide accurate and up-to-date information based on the specific formulation and usage guidelines of the paint.



CONTACT

If you are dissatisfied with this product, contact our Product Support Department at
info@dwilpainting.com

