SERVEREDGE

Dual DVI KVM Extender, PS/2, USB, Serial with Audio

over UTP - Up to 100m

Part No: EKDD-S

PRODUCT DESCRIPTION

The Serveredge Dual-View KVM Extender consists of a Console Unit and a Computer Unit that is suitable to Remotely locate the keyboard, mouse and monitor up to 100 meters away from a computer via Category5 /5e/ 6 UTP/ STP/ FTP cable with the maximum resolution of 1920 x 1200. Even more, it provides optional functions of audio and serial control.

The exclusive serial features instant data communication or Touch Screen function. It supports H/W and S/W (Xon / Xoff) Handshake (selectable) with the serial speed up to 115.2Kbps/ 921.6Kbps (max.).

PRODUCT SPECIFICATION

EKDD-S		Console Unit	Computer Unit
Video Resolution (max.)		WUXGA (1920 x 1200) / UXGA (1600 x 1200)	
Extension Distance (max.)		100 meters	
Unit Connection		CAT5-RJ45 Female x 2	
Keyboard / Mouse		USB-A x 2	PS/2 x 1, USB-B x 1
Video		DVI-Female x 2 (Connect to monitor)	DVI-Female x 2 (Connect to computer)
Audio Jack (Speaker + Mic)		1 Set	
Serial	Connector	DB-9 Male x 1, DTE	DB-9 Female x 1, DCE
	Rotary DIP Switch	x 1 (Baud rate selection)	n/a
	DIP Switch	x 1 (Data format selection)	n/a
Remote Control Jack		x 1 for IR Receiver	x 1 for IR Transceiver
LED Indicator		Link 1 x 2 (CAT5 1 status, Data transfer status) Link 2 x 2 (CAT5 2 status, Data transfer status)	
Power Supply		External Power Adapter DC 12V	
Weight (g)		500 ~ 520 (each unit)	
Power Supply		22 x 140 x 100 (each unit)	

PRODUCT FEATURES

> Remotely locate the keyboard, mouse and monitor up to 100 meters away from a computer via Category5 / 5e / 6 UTP/ STP/ FTP cable

> Support the dual-view function which can split your window (browser/ work area...) into two

- > IR extension available
- > Support surge protection
- > Support HID standard keys
- > No drivers needed or software required

> Support high resolution of up to 1920 x 1200 (WUXGA), 1920 x 1080 (Full HD)

> Compatible with most of the popular screen resolution to XGA, SXGA, UXGA, WSXGAWUXGA system



Exclusive Serial Function

> Serial interface for instant data communication or Touch Screen function

- > Full-Duplex data communication
- > Support H/W and S/W (Xon / Xoff) Handshake (selectable)
- > Serial speed up to 115.2Kbps/ 921.6Kbps (max.)



© 2014 SERVEREDGE. All rights reserved. Reproduction in whole or in part without permission is prohibited. All other trademarks are the properties of their owners. Tested to Comply with FCC and CE Standards. HOME OR OFFICE USE.