

## 19" LCD KVM CONSOLE RACK DRAWER

- 8 PORT KVM VGA/USB/PS2 WITH OPTIONAL IP ACCESS

PART NUMBER: [SED-KLVGA-0819V2](#)



### PRODUCT DESCRIPTION

The Serveredge KVM console integrates a 19" Wide Screen LCD display, slim keyboard and a mouse touchpad to manage single or multiple computers across a network. The KVM uses only 1RU of rack space, delivering a space friendly solution for complete management.

#### Space Friendly & Less Clutter

1RU of rack space is all it requires, allowing extra storage area so your cabinet rack will be much more organised. Just slide open the 19" console display when it is required and close after use and slide back into place. The KVM can also be mounted onto your cabinet rack as an option.

#### Reduce IT cost & maximise budget

Serveredge LCD KVM console provides all the essential equipment to allow you to manage multiple computer(s) at an affordable cost. There's no need to spend on multiple displays and keyboards as you will only require the one console to manage and control productivity.

#### Quick Assembly and Warranty

The LCD KVM's comes with a user friendly quick installation manual and 2 year warranty for the extra piece of security.

### PACKAGING INCLUDES

- 1 x User manual
- 2 x Mounting bracket
- 2 x Lock ear
- 2 x Install screws
- 1 x Power adapter
- 1 x Power Cable
- 8 x KVM Cable (SED-LVPU-1.8) VGA/PS2/USB

### PRODUCT FEATURES

- Front LCD Console (keyboard, mouse, monitor 19" ) + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- Optional IP module (SED-LIPV2) can be installed in the designated IP slot.
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm

### GUARANTEE/WARRANTY

Serveredge products are manufactured at the highest standards using highest quality materials at an affordable price. This Serveredge product comes with a 2 year warranty standalone or a 25 years warranty as part of a certified structured cabling project. Subject to Serveredge Terms and Conditions\*

**19" LCD CONSOLE SPECIFICATION**

Type	18.51" Wide-Screen LCD Console	
LCD Monitor	Ratio	18.51" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	409.8(H) x 230.4(V)
	Resolution	1366*768 @60HZ(Optimum)/1920*1080@60HZ(Max)
	Support Color	16.7M, True 8 bit
	Contrast	1000 : 1 (Typ)
	Back light	LED
	Pixel Pitch	300*300um
	LED MTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension	D407 *W445 *H45mm	
Weight	6.07kg	

**KVM MODULE SPECIFICATION**

Type	8 Port	
Model No.(Completed device)	SED-KLVGA-0819V2	
Computer Connection	Direct Connects	8
	Maximum Connects	128
CPU Port Selection	OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)	
Connectors	Console Connector	
	DB 37PIN	
	PC Connector	Monitor, Keyboard/ Mouse Switch Module
	8 x VGA DB15, Female Blue	
	Power	
1 x DC Jack		
Network Port		1 x RJ45(Optional)
Key Switch	Connection Port Selection	KVM Operation Panel Digital keys
	KVM Reset	KVM Operation Panel Function Keys
	IP Module Reset	1 x semi-embedded key
	IP Module Default	1 x semi-embedded key
LED's	Selected	Nixie Tube Display
	Online	8 x Red
	IP Network	1 x Green, 1 x Orange
Analog Mode	Keyboard/Mouse	USB, PS/2
Resolution (Max)	1920 x 1200 @ 60HZ Local & Remote	
Scan time interval	3, 5, 10, 15, 20, 30, 40, 60s (3s by default)	
Operating Environment	Operating temperature	-10-50°C
	Storage temperature	-20-60°C
	Humidity	0-80%RH, No Condensation
Physical Properties	Housing	Metal
	Dimension	D1484 *W445 *H45mm
	Weight	3.32kg