

19" LCD CAT6 KVM CONSOLE RACK DRAWER

- 16 PORT CAT5e / CAT6 KVM USB/PS2/VGA WITH OPTIONAL IP ACCESS

PART NUMBER: [SED-KLC6-1619V2](#)



PRODUCT DESCRIPTION

The Serveredge SED-KLC6-1619 rack console features a 19" Widescreen A Grade LCD screen and an integrated CAT5 / CAT6 - 16 port KVM switch. The keyboard is a 104 key notepad keyboard. This state-of-the-art modular rack console offers a space saving, streamlined approach to your rack environment by integrating your LCD monitor, KVM switch, Keyboard, and Mouse options in one unit.

Setup is fast and easy. Simply plug in this cutting edge modular rack console with integrated KVM and you are ready to go. To use, slide the rack console unit out and open the cover to reveal the widescreen monitor and built-in keyboard and mouse. To conserve valuable rack space, close the cover and slide the console module back out of the way when finished. Product comes with 2 Year warranty.

PACKAGING INCLUDES

- 1 x User manual
- 2 x Mounting bracket
- 2 x Lock ear
- 2 x Install screws
- 1 x Power adapter
- 1 x Power Cable
- 16 x VGA/USB over CAT5e / CAT6 Dongle (SED-USB-C6)

PRODUCT FEATURES

- Front LCD Console (keyboard, mouse, monitor 19") + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- Optional IP module (SED-LIPV2) can be installed in the designated IP slot.
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm

GUARANTEE/WARRANTY

Serveredge products are manufactured at the highest standards using highest quality materials at an affordable price. This Serveredge product comes with a 2 year warranty standalone or a 25 years warranty as part of a certified structured cabling project. Subject to Serveredge Terms and Conditions*

19" LCD CONSOLE SPECIFICATION

Type	18.51" Wide-Screen LCD Console	
LCD Monitor	Ratio	18.51" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	409.8(H) x 230.4(V)
	Resolution	1366*768 @60HZ(Optimum)/1920*1200@60HZ(Max)
	Support Color	16.7M, True 8 bit
	Contrast	1000 : 1 (Typ)
	Back light	LED
	Pixel Pitch	300*300um
	LED MTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension	407*445*45mm	
Weight	6.07kg	

KVM MODULE SPECIFICATION

Type	16 Port		
Model No.(Completed device)	SED-KLC6-1619V2		
Computer Connection	Direct Connects	16	
	Maximum Connects	256	
CPU Port Selection	OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)		
Connectors	Console Connector		
	DB 37PIN		
	PC Connector	Monitor, Keyboard/ Mouse Switch Module	16 x VGA DB15 Female Blue, 16 x USB OR 16 x PS/2
	Switch Module Port		16 x RJ45
	Power		1 x DC Jack
	Network Port		1 x RJ45(Optional)
Key Switch	Connection Port Selection		
	KVM Operation Panel Digital keys		
	KVM Reset		
	KVM Operation Panel Function Keys		
LED's	IP Module Reset	1 x semi-embedded key	
	IP Module Default	1 x semi-embedded key	
	Selected	Nixie Tube LED Display	
Analog Mode	Online	16 x Red	
	IP Network	1 x Green, 1 x Orange	
	Keyboard/Mouse	USB, PS/2	
Resolution (Max)	1920 x 1200 @ 60HZ Local & Remote		
Scan time interval	3, 5, 10, 15, 20, 30, 40, 60s (3s by default)		
Operating Environment	Operating temperature	-10-50°C	
	Storage temperature	-20-60°C	
	Humidity	0-80%RH, No Condensation	
Physical Properties	Housing	Metal	
	Dimension	148.4*445*45mm	
	Weight	3.80kg	