

ULTRA PRECISION GROUND TEETH

HIGH TOLERANCE BALANCED SET STATE OF THE ART TOOTH HARDENING







WOODMAXX BLADE PROFILES & SIZES Width x Thickness		Hook Angle							×	ă
		10°				7°	4°	7/40°	Лах	SweepMaxx
		Tooth Spacing						PalletMaxx	des	
		1/2" (2 TPI)	3/4" (1.3 TPI)	7/8" (1.1 TPI)	1" (1 TPI)	7/8" (1.1 TPI)	7/8" (1.1 TPI)	7/8" (1.1 TPI)	Pal	Swe
1" x .042"	25.4 mm x 1.07mm	•	~							•
1-1/8" x .035"	28.6 mm x .89 mm	~	>							~
1-1/4" x .042"	31.8 mm x 1.07 mm		~	~	~	~	~	~	~	~
1-1/4" x .045"	31.8 mm x 1.14 mm			>	•	~	>			
1-1/2" x .042"	38 mm x 1.07 mm			~	•	•	•	•		
1-1/2" x .050"	38 mm x 1.27 mm			~	•	~	~	~		
1-1/2" x .055"	38 mm x 1.4 mm			~	•	~	~	~		
2" x .042"	50.8 mm x 1.07 mm			•	>	•	•	•		
2" x .050"	50.8 mm x 1.27 mm			•	>	•	•	~		
2" x .055"	50.8 mm x 1.4 mm				•	•		~		



- >> Best quality steel for extended life
- >> Precision-ground teeth & smooth welds
- >> Available in coil or custom length blades

HOOK ANGLE GUIDE

- 10° All-purpose & mixed hardwoods
- 7° Mixed hardwoods, seasoned, difficult
- 4° Extreme hardwoods, exotic, frozen
- 7/40° High horsepower production



- >> Dismantle pallets quickly and efficiently
- >> Aggressive carbon steel teeth
- >> Available in coil or custom length blades





- >> Double-staggered tooth edge
- >> Sweeps sawdust away as it cuts
- >> Hard & soft woods, frozen & dry



