

testo 317-3 CO monitor

Instruction manual

en





Please read this document carefully and make sure you are familiar with how to operate the product before putting it to use. Keep this document close at hand so you can refer to it if necessary.

### Safety information

General information

### Avoid electrical hazards:

► Never take measurements with the unit and its external probes on or near live components unless the unit is expressly approved for current and voltage measurements.

### ⚠ Protect the instrument:

▶ Never store the unit together with solvents (e.g. acetone).

### Preserve the product safety/warranty entitlement:

- ▶ Operate the unit only within the parameters specified in the
- ▶ Handle the unit suitably and according to its intended purpose.
- ► Never apply force!
- ▶ Open the unit only when this is expressly described in the Instruction manual for maintenance purposes.

### Ensure correct disposal:

- ▶ Dispose of defective rechargeable batteries and spent batteries at the collection points provided.
- Send the unit directly to us at the end of its life cycle. We will ensure that is it disposed of in an environmentally friendly

### Intended use

The testo 317-3 CO monitor determines the existence of carbon monoxide (CO) in the environment and warns the user visibly and audibly about dangerous gas concentrations,





Do not use testo 317-3 as a monitoring instrument for personal

### Technical data

Feature	Values
Measurement range	±0 to +1999ppm
Resolution	1ppm
Accuracy	±10ppm at ±0+99ppm ±10% at +100+499ppm ±20% at >500ppm
Response time t <sub>90</sub>	40s
Power supply	2 batteries, type Micro AAA 1.5 V
Battery life	150h (audible CO display switched off), once   appears: approx. 1h
Transport/storage temp.	-20 to +50°C
Ambient temperature	-5 to +45°C
CE guideline	89/336/EEC
Warranty	2 years for instrument 3 years for CO sensor

#### Included

testo 317-3, carrier case with belt clip, headphones, hand loop, Instruction manual.

### Care and Maintenance

### Changing the battery

- 1 Open battery compartment.
- 2 Remove empty batteries and replace with new ones. Pay attention to +/-



#### Clean instrument

▶ If the instrument housing is soiled, clean with a damp cloth (soap lye). Do not use any aggressive cleaning solutions!

### **Troubleshooting**


Fault	Possible causes	Remedy
Iights in display.	Batteries are almost spent.	Change batteries.
Instrument cannot be switched on.	Batteries are spent.	► Change batteries.
Ecc lights up in display.	Instrument defect.	Switch off instrument and contact Testo Customer Service or your dealer.
Loudspeaker does not work.	Headphones are connected.	► Disconnect headphones.

## Spare parts

Name	Part no.
Carrying loop	0516.3181
Carrying case with belt clip	0516.0317
Headphones	0554.0946


### Operation


### Switching on




# Switching off Measurement view Instrument off


### Setting alarm limit







### Switching audible CO display on/off



#### Measuring





Position the instrument such that the opening for the (orange) comes into ambient air flows. The opening should not be completely


closed over. The reading is updated once a second.

#### Alarm value exceeded



is deactivated once the alarm sound is switched off! Switch on again:

#### Hold reading, display maximum value



# Zero point is stored until instrument is switched off. **+** ppm

Measurement view

Sensor is zeroed.

### Notes on carbon monoxide

Carbon monoxide is a highly toxic gas for humans even in very low concentrations.

It is invisible, tasteless and odourless.

Zeroing sensor

Measurement view

The following table gives you a summary of the effects which specific CO concentrations in the air have on humans.

Concentration in the air		Inhalation time and effects*	
30 ppm	0.003 Vol.%	Max. workplace concentration during an 8 hour working day (limit value for Germany)	
200 ppm	0.02 Vol.%	Light headache within 2-3h	
400 ppm	0.04 Vol.%	Ache in forehead area within 1-2h, spreading to whole head area	
800 ppm	0.08 Vol.%	Dizziness, nausea and limb twitching within 45min, unconscious withing 2h	
1600 ppm	0.16 Vol.%	Headache, dizziness, nausea within 45min, dead within 2h	
3200 ppm	0.32 Vol.%	Headache, dizziness, nausea within 5-10min, dead within 30min	
6400 ppm	0.64 Vol.%	Headache, dizziness, nausea within 1-2min, dead within 10-15min	
12800 ppm	1.28 Vol.%	Dead within 1-3min	

\* The above concentrations are approximate values. Humans react differently to CO concentrations depending on height, age, sex and state of physical health

testo AG does not accept any responsibility for the accuracy of the above data.