



KRASO® Sealing Insert Type SD
Check the installation video
(just scan the QR code!)



KRASO® Type SD 30



KRASO® Type SD 30 - T



KRASO® Type SD 30 - GF



KRASO® Type SD 60



KRASO® Type SD 60 - T



KRASO® Type SD 60 - GF



KRASO® Sealing Insert Type SD

The solution for special situations

Usually ready for dispatch within 24 hours!

- + For core drillings and casings
- + Individual and custom-made solution: with large flange or split!
- + **KRASO® Sealing Insert quality: 5 mm thick clamping plates made of non-corrosive stainless steel V2A, 30 or 60 mm seal made of a specially developed rubber mixture, welded-on studs instead of through bolts**
- + Torque Control Nut **KRASO® DKM: integrated torque limiter - no torque wrench required!**
- + **MPA-tested: protects reliably against pressing water up to 2.5 bar / 5 bar!**
- + **Gas- and odour-tight** – high-quality in terms of TA-Air!
- + **Radon tightness IAF tested** - meets the requirements for radon precautionary areas according to FHRK leaflet MB 101!
- + **Tested according to FHRK test specification GE 101!**
- + With arrangement template: **see the arrangement of media pipes, pipes and cables at a glance!**
- + **Generally available within 24 hours!**
- + Available at an additional charge: **stainless steel V4A / KTW - recommendation / NBR - oil- and petrol-resistant / temperature resistant up to 220 °C**
- + **DafStB waterproof concrete guideline: stress class 1 + 2**

KRASO® Sealing Insert Type SD 30 • KRASO® Sealing Insert Type SD 60 **LG 1**

for installation of pipes or cables, Torque Control Nut **KRASO® DKM*** | DafStB waterproof concrete guideline: stress class 1 + 2

KRASO® Type SD 30 / KRASO® Type SD 30 - T, split / KRASO® Type SD 30 - GF, large flange

KRASO® Type SD 60 / KRASO® Type SD 60 - T, split / KRASO® Type SD 60 - GF, large flange

Core drilling / casing in mm (from - to)	50 (49 - 52)	60 (59 - 62)	70 (69 - 72)	80 (79 - 83)	100 (99 - 103)	125 (124 - 128)	150 (149 - 153)	200 (198 - 203)	250 (248 - 253)	300 (298 - 303)	350 (348 - 353)	400 (398 - 403)	450 (448 - 453)	500 (497 - 503)
	max. external diameter pipe or cable													
from	0	0	0	0	0	0	0	0	0	0	0	0	0	0
to	25	35	45	55	75	100	125	175	225	275	325	375	425	475
KRASO® Type SD 30														
KRASO® Type SD 30	91 €	91 €	91 €	98 €	98 €	125 €	142 €	184 €	248 €	317 €	380 €	435 €	513 €	571 €
KRASO® Type SD 30 - T	105 €	105 €	105 €	113 €	113 €	144 €	163 €	212 €	285 €	364 €	437 €	500 €	590 €	656 €
KRASO® Type SD 30 - GF	100 €	100 €	100 €	108 €	108 €	138 €	156 €	202 €	272 €	348 €	418 €	478 €	564 €	628 €
Surcharge: additional drilling	up to 5 drillings each additional drilling 17 €, each further additional drilling 11 €													
KRASO® Type SD 60														
KRASO® Type SD 60	122 €	131 €	131 €	131 €	140 €	172 €	202 €	261 €	339 €	444 €	516 €	575 €	680 €	795 €
KRASO® Type SD 60 - T	141 €	150 €	150 €	150 €	161 €	198 €	232 €	300 €	389 €	511 €	594 €	661 €	782 €	915 €
KRASO® Type SD 60 - GF	134 €	144 €	144 €	144 €	154 €	190 €	222 €	287 €	372 €	489 €	568 €	632 €	748 €	875 €
Surcharge: additional drilling	up to 5 drillings each additional drilling 17 €, each further additional drilling 11 €													

* In some cases, allen screws must be used due to the design

All sizes and diameters available on request!