

FIXTURE CONNECTION INSTRUCTIONS

For RGBC5 WaterGlow Lighting



This LED Color Changing RGB Light Kit was shipped with the fixtures disconnected from the cord in order to avoid product damage during shipping. Each fixture includes a quick disconnect coupling and a heat-shrink tube.

PARTS OVERVIEW



INSTRUCTIONS

To connect each light fixture to the power cord:

1. Remove protective caps from the female (Cord Splitter side) half of the connection.
2. Confirm the o-ring is present on the male (Fixture) side of the connection. If the o-ring is missing, check the fixture box in case it came loose during shipping. If you are unable to locate the o-ring, use the spare that is provided in the kit. The connection will not be water-tight without the o-ring in place.
3. Slide the Shrink Tube over the female connector of the Cord Splitter and slide it down the cord towards the splitter, exposing the connector for assembly.



INSTRUCTIONS (CONT.)

4. Connect the male Fixture connector to the female Cord Splitter connector.



5. Slide the Connector Nut from the male Fixture half of the connector over until it engages the threads on the female Cord Splitter half of the connector. Turn clockwise to secure the two halves together. Turn by hand until tight. (Caution: Over-tightening may damage components.)



6. Slide the Shrink Tube over the cord connection and center it on the connection.



7. Use a heat gun to shrink the tubing down to secure the connection and create an additional seal against water intrusion. (Do not apply excessive heat directly to shrink tube or assembly, as overheating may result in damage to components.)



8. Repeat for each additional fixture.