



Features and Benefits

The three heavily aerated, conical displays of this series create an impressive pyramid of water. The height proportions can be varied by the adjustment of valves regulating each pod, allowing on site modifications.

HP	1ST HT	2ND HT	3RD HT	Diameter	1 Phase (V)	3 Phase (V)		
10	15'	10'	6'	8'	230	208	230	460
15	18'	12'	8'	9'	230	208	230	460
20	22'	15'	10'	10'	—	208	230	460
30	25'	18'	12'	12'	—	208	230	460

NOZZLES

- ◆ Precision machined brass/bronze or stainless steel nozzles

PUMPS/MOTORS

- ◆ High performance turbine pump/motor assembly
- ◆ Stainless steel construction
- ◆ Water cooled: no oils, seals or o-rings to replace
- ◆ **4 year warranty**

FLOTATION

- ◆ Rotocast polypropylene with UV inhibitors for long life
- ◆ Individual leveling compartments for exact adjustments
- ◆ **4 year warranty**

CONTROL PANEL

- ◆ UL listed per National Electrical Code
- ◆ Weatherproof steel enclosures

SUBMERSIBLE LIGHT FIXTURES

- ◆ Energy efficient LED, 140 lumens/watt
- ◆ Stainless steel housing
- ◆ **2 year warranty**

CABLES

- ◆ STW-A rated
- ◆ **4 year warranty**