

Product Data Sheet

No. 3860 - 01/22

GLASS CLEANER

CARB <10% VOC (AEROSOL)

PRODUCT NUMBERS: 860 - 19 OZ. NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: Aervoe Glass Cleaner is an industrial cleaner that is effective on a variety of glass-based surfaces. It is packaged with a 360° spray anyway valve allowing for application in tough spaces. The fast-working foam cuts through dirt, grease, and grime. Wipes off to a bright and sparkling, streak-free finish. Cleans all glass and Plexiglas objects, leaving an invisible, dust-repelling shield that retards fogging. Non-streaking, fast action cleaner for economical applications.

Benefits: Glass Cleaner does not leave a film, contains no ammonia, retards fogging, removes smoke haze and is harmless to painted surfaces. This fast-acting formulation even removes fingerprints. Will also cut through greasy residue and factory film.

Application: Use to clean all glass including mirrors, windshields and Plexiglas.

Directions: For best results product should be used at temperatures between 60° and 80°F (16° and 27°C). Align spray head with black mark on valve rim to ensure complete evacuation. Before spraying, shake can vigorously for 2 seconds. Hold can in an upright position, 8 to 12 inches from surface to be cleaned and spray using a sweeping motion.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc.

Packaging:

Aerosol:

Cans (211x713)

19 oz. net wt. (540 g)

20.0 fl. oz. (561 ml)

12 cans/case

19 lbs. (8.6 kg)

0.47 CF (0.013 CM)



Aervoe Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aervoe.com • mailbox@aervoe.com

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Foamy liquid

Odor:

Citrus

Performance and Chemical Properties:**Aerosol**

| | |
|--|---------------------------|
| Weight per gallon | 7.9 lbs |
| Specific gravity | 0.95 |
| Flammability: Label marking | Flammable |
| Flash point..... | (0°F (-17.8°C)) |
| Application temperature (air & substrate)..... | 60° to 80°F (16° to 27°C) |
| Active ingredients by weight..... | 96% |
| Volatile Organic Compound limit (CARB)..... | <10% |
| Surface tension | Low |

Base Materials

| | |
|------------------------|---|
| Top Two..... | Water, Ethylene Glycol Monobutyl Ether |
| Propellant System..... | Hydrocarbon |

III. SHIPPING, STORAGE AND HEALTH

| | |
|--------------------------------------|---------------------------|
| | Aerosol |
| UN number..... | UN 1950 |
| Proper shipping description..... | Aerosols |
| Hazardous class..... | 2.1 |
| Packing group | N/A |
| Limited quantity | Yes |
| Warehouse storage level number | NFPA 30B Level 1 |
| Storage temperature | 32° to 120°F (0° to 49°C) |
| Shelf life | 1 to 5 years |
| HMIS ratings | |
| Health | 2 |
| Fire | 4 |
| Reactivity..... | 1 |

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.