SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

### 1 Identification

- · Product identifier
- · Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)
- · Article number:

A16015, A16018, A16508, A16515, A16518, A16525, A16528, A16535, A16538, A16545, A16548, A16565, A16568, A16578, A16585, A16588, A16595, A16598, A16705, A16708, A16715, A16718, A16726, A16728, A16815, A16825, A16855, A16875, A16879, A16885, A16905, A16910, A16915, A16920, API0246, API0248

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

**URETHANE POLYMER** 

Tetraethylene Glycol Di 2-ethylhexoate

Propylene glycol

dipropylene glycol butyl ether

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

*P264 Wash thoroughly after handling.* 

(Contd. on page 2)



Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. P332+P313 P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
	URETHANE POLYMER	13-30%
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate	1.5-5%
107-98-2	1-methoxy-2-propanol	1.5-5%
57-55-6	Propylene glycol	1-1.5%
29911-28-2	dipropylene glycol butyl ether	1-1.5%

## 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 2)

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

107-98-2	1-methoxy-2-propanol	100 ppm
57-55-6	Propylene glycol	30 mg/m
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m
1333-86-4	Carbon black	9 mg/m³
124-68-5	2-amino-2-methylpropanol	17 mg/m
PAC-2:		
107-98-2	1-methoxy-2-propanol	160 ppm
57-55-6	Propylene glycol	1,300 mg/m
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m³
1333-86-4	Carbon black	99 mg/m³
124-68-5	2-amino-2-methylpropanol	190 mg/m³
PAC-3:		
107-98-2	1-methoxy-2-propanol	660 ppm

-USA

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

ſ	57-55-6		(Contd. of page 3) $7,900 \text{ mg/m}^3$
t	112926-00-8	precipitated Silica (Silica-Amorphous)	$1,200 \text{ mg/m}^3$
	1333-86-4	Carbon black	590 mg/m³
	124-68-5	2-amino-2-methylpropanol	570 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

107-98	107-98-2 1-methoxy-2-propanol	
REL	Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm	
TLV	Short-term value: 369 mg/m³, 100 ppm	
57.55	Long-term value: 184 mg/m³, 50 ppm	
	57-55-6 Propylene glycol	
WEEL	Long-term value: 10 mg/m <sup>3</sup>	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 4)

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

0 D1	1		4.
y Physian	i ana c		
9 Physica	i unu ci	וטעטוע	uucs

· Information	on basic	nhysical	and ch	omical	nronerties
· Inioimanon	on vasic	pnysicui	- ини сп	iemicui	properties

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

**Melting point/Melting range:** Undetermined. **Boiling point/Boiling range:** 100 °C

• Flash point: 96 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 270 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

(Contd. on page 6)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

	(Contd. of	page 5
· Vapor pressure at 20 °C:	23 hPa	
· Density at 20 °C:	1.02235 g/cm³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wo	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	4.9 %	
Water:	48.8 %	
VOC content:	4.87 %	
	99.2 g/l / 0.83 lb/gal	
Solids content:	41.4 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1333-86-4	Carbon black	2 <i>B</i>
		(Contd. on page 7)

(Contd. on page 7)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
· Packing group · DOT, ADR, IMDG, IATA	Void	
· Environmental hazards: · Marine pollutant:	No	

(Contd. on page 8)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": Void

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

Acrylic Resin

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

- · TSCA (Toxic Substances Control Act):
- 18268-70-7 Tetraethylene Glycol Di 2-ethylhexoate
  - 107-98-2 1-methoxy-2-propanol
  - 57-55-6 Propylene glycol
- 29911-28-2 dipropylene glycol butyl ether
- 1333-86-4 Carbon black
- 51200-87-4 4,4-dimethyl-1,3-oxizalidine
- 53320-86-8 CLAY
  - 143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol
- 8042-47-5 White mineral oil, petroleum
- 124-68-5 2-amino-2-methylpropanol
- 7732-18-5 water
- · TSCA new (21st Century Act) (Substances not listed)

URETHANE POLYMER

- · Proposition 65
- · Chemicals known to cause cancer:

1333-86-4 Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

SEM

Printing date 10/22/2018 Version number 20 Reviewed on 10/22/2018

Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 8)

#### · TLV (Threshold Limit Value established by ACGIH)

1333-86-4 Carbon black

*A4* 

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



#### · Signal word Warning

#### · Hazard-determining components of labeling:

**URETHANE POLYMER** 

Tetraethylene Glycol Di 2-ethylhexoate

Propylene glycol

dipropylene glycol butyl ether

#### · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### · Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

*P264* Wash thoroughly after handling.

*Use only outdoors or in a well-ventilated area.* 

*P280* Wear protective gloves / eye protection / face protection.

*P302+P352 If on skin: Wash with plenty of water.* 

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364

Take off contaminated clothing and wash it before reuse.
P332+P313

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- Date of preparation / last revision 10/22/2018 / 19

(Contd. on page 10)

SEM

Printing date 10/22/2018 Version number 20

Reviewed on 10/22/2018

## Trade name: A16015-A16920 Aerospace Sure-Coat Color (non-aluminum colors)

(Contd. of page 9)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

USA