

# SAFETY DATA SHEET

## Bulldog Sealer & Adhesion Promoter

Page: 1

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Bulldog Sealer & Adhesion Promoter	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact:</b>	3E 24 Hour Emergency Contact	(800)451-8346
<b>Information:</b>	W.M. Barr Customer Service	(800)398-3892
<b>Intended Use:</b>	Paint adhesion.	
<b>Synonyms:</b>	GBDS12326, QBDS12327	
<b>Additional Information</b>	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

### 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2  
Acute Toxicity: Inhalation, Category 4  
Skin Corrosion/Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 2  
Germ Cell Mutagenicity, Category 1A  
Carcinogenicity, Category 1B  
Toxic To Reproduction, Category 2  
Specific Target Organ Toxicity (single exposure), Category 3  
Specific Target Organ Toxicity (repeated exposure), Category 2



**GHS Signal Word:** Danger

**GHS Hazard Phrases:** H225: Highly flammable liquid and vapor.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H340: May cause genetic defects.  
H350: May cause cancer.  
H361: Suspected of damaging fertility or the unborn child.  
H373: May cause damage to organs through prolonged or repeated exposure.

**GHS Precaution Phrases:** P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe gas/mist/vapors/spray.  
P264: Wash hands thoroughly after handling.

## Bulldog Sealer &amp; Adhesion Promoter


Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

**GHS Response Phrases:**

P271: Use only outdoors or in a well-ventilated area.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P281: Use personal protective equipment as required.  
 P235: Keep cool.  
 P302+352: IF ON SKIN: Wash with plenty of soap and water.  
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+313: IF exposed or concerned: Get medical attention/advice.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P314: Get medical attention/advice if you feel unwell.  
 P321: Specific treatment label.  
 P332+313: If skin irritation occurs, get medical advice/attention.  
 P337+313: If eye irritation persists, get medical advice/attention.  
 P362: Take off contaminated clothing and wash before re-use.  
 P370+378: In case of fire, use dry chemical powder to extinguish.  
 P403+233: Store container tightly closed in well-ventilated place.  
 P405: Store locked up.  
 P501: Dispose of contents/container according to local, state and federal regulations.

**GHS Storage and Disposal Phrases:****Hazard Rating System:****OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

**Potential Health Effects (Acute and Chronic):**

**Skin Contact:**  
 Harmful is absorbed through the skin. Contact with the skin may cause mild to moderate skin irritation, defatting and drying of the skin, and allergic dermatitis. Symptoms may include redness, swelling, and burning of the skin.

**Eye Contact:**  
 This material is an eye irritant. May cause irritation, stinging, tearing, redness, swelling, pain and blurred vision.

**Inhalation:**  
 Vapors can be harmful if inhaled. Effects from exposure may include headaches, dizziness, fatigue, and nausea. High concentrations may result in central nervous system depression, irritation to the respiratory tract, and pulmonary edema.

**Ingestion:**  
 Harmful or fatal if swallowed. Effects from exposure through ingestion may include gastrointestinal disturbances, pain, discomfort, gastrointestinal irritation, nausea, vomiting, diarrhea, irritation to the mouth, throat, and stomach. Other effects may produce central nervous system effects, such as dizziness, loss of balance and coordination, unconsciousness, coma, and even death.

**Chronic Effects:** Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.

**Medical Conditions Generally** Skin, eye, liver, kidney, nervous system, respiratory, lung (asthma-like conditions).

# SAFETY DATA SHEET

## Bulldog Sealer & Adhesion Promoter

Page: 3

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

### Aggravated By Exposure:

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
540-88-5	Tert-Butyl acetate {Acetic acid, tert-butyl ester; Acetic acid, 1,1-dimethylethyl ester}	Proprietary	AF7400000
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	Proprietary	WL3675000
108-88-3	Toluene {Benzene, Methyl-; Toluol}	Proprietary	XS5250000
108-38-3	m-Xylene {Benzene, m-Dimethyl-}	Proprietary	ZE2275000
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	Proprietary	DA0700000
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	Proprietary	ZE2450000
106-42-3	p-Xylene {Benzene, p-Dimethyl-}	Proprietary	ZE2625000
98-56-6	4-Chlorobenzotrifluoride {4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene}	Proprietary	XS9145000
79-20-9	Methyl acetate (Methyl ester of acetic acid)	Proprietary	AI9100000
110-43-0	2-Heptanone {Methyl pentyl ketone; n-Amyl methyl ketone}	Proprietary	MJ5075000
67-64-1	Acetone {2-Propanone}	Proprietary	AL3150000
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	Proprietary	WJ8925000
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	Proprietary	CZ9370000
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	Proprietary	KJ8575000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

## 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:** Skin:  
Remove contaminated clothing. Wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.

Eyes:  
Immediately flush eyes with water for at least 15 minutes. Seek medical attention.

Inhalation:  
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:  
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Signs and Symptoms Of Exposure:** See Health Hazards.

**Note to Physician:** Treat symptomatically. Treatment of overexposure should be directed at the control of the symptoms and the clinical condition of the patient.

## 5. FIRE FIGHTING MEASURES

<b>Flash Pt:</b>	IB 45.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Autoignition Pt:</b>	No data.
<b>Suitable Extinguishing Media:</b>	Use alcohol foam, carbon dioxide, or dry chemical powder.
<b>Unsuitable Extinguishing Media:</b>	Do not use a solid water stream, as this may spread the fire.
<b>Fire Fighting Instructions:</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. Containers exposed to heat may pressurize. Stay away from the heads of exposed containers. Use water spray to cool fire exposed containers. Vapors are heavier than air.
<b>Flammable Properties and Hazards:</b>	Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Steps To Be Taken In Case Material Is Released Or Spilled:</b>	<p>Clean up spills immediately, observing precautions in Protective Equipment section.</p> <p>Isolate the hazard area and deny entry. Keep unnecessary people away. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep ignition sources out of the hazard area.</p> <p>Small spills: Absorb the liquid with inert material, such as sand, earth, or other noncombustible material and place into a compatible container for disposal.</p> <p>Large spills: Dike far ahead of the spill for later disposal.</p> <p>Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.</p>
---	---

## 7. HANDLING AND STORAGE

<b>Precautions To Be Taken in Handling:</b>	<p>"Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.</p> <p>Keep away from sources of ignition. Ground and bond containers when transferring material.</p>
<b>Precautions To Be Taken in Storing:</b>	Keep container closed when not in use. Do not store in direct sunlight. Store in a tightly closed container. Store in cool, dry area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Bulldog Sealer &amp; Adhesion Promoter

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
540-88-5	Tert-Butyl acetate {Acetic acid, tert-butyl ester; Acetic acid, 1,1-dimethylethyl ester}	PEL: 200 ppm	TLV: 200 ppm	No data.
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	PEL: 100 ppm STEL: 600 ppm/(5min/3hr) CEIL: 200 ppm	TLV: 20 ppm STEL: 40 ppm	No data.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
108-38-3	m-Xylene {Benzene, m-Dimethyl-}	No data.	TLV: 100 ppm STEL: 150 ppm	No data.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	No data.	TLV: 100 ppm STEL: 150 ppm	No data.
106-42-3	p-Xylene {Benzene, p-Dimethyl-}	No data.	TLV: 100 ppm STEL: 150 ppm	No data.
98-56-6	4-Chlorobenzotrifluoride {4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene}	No data.	No data.	No data.
79-20-9	Methyl acetate (Methyl ester of acetic acid)	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
110-43-0	2-Heptanone {Methyl pentyl ketone; n-Amyl methyl ketone}	PEL: 100 ppm	TLV: 50 ppm	No data.
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	PEL: 500 ppm	TLV: 100 ppm	No data.
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	No data.	TLV: 10 ppm	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	No data.

**Respiratory Equipment (Specify Type):** A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

A dust mask does not provide protection against vapors.

**Eye Protection:** Safety glasses, with sideshields, chemical goggles or faceshields are recommended to safeguard against potential eye contact.

**Protective Gloves:** Wear impermeable gloves.

**Other Protective Clothing:** Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.

**Engineering Controls (Ventilation etc.):** Use only with adequate ventilation to prevent the buildup of vapors. Do not use in areas where vapors can accumulate and concentrate. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area away from the individual. If strong odor is noticed or you experience slight dizziness, headache, nausea, or other signs of inhalation exposure, STOP. The ventilation is inadequate. Leave the area immediately.

# SAFETY DATA SHEET

## Bulldog Sealer & Adhesion Promoter

Page: 6

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

### Work/Hygienic/Maintenance Practices:

A source of clean water should be available in the work area when handling this product. Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Liquid, cloudy, light yellow.
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	200.00 F
<b>Autoignition Pt:</b>	No data.
<b>Flash Pt:</b>	45.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Specific Gravity (Water = 1):</b>	0.945 - 0.970
<b>Density:</b>	7.971 LB/GL
<b>Vapor Pressure (vs. Air or mm Hg):</b>	9.5 MM HG at 20.0 C
<b>Vapor Density (vs. Air = 1):</b>	> 1
<b>Evaporation Rate:</b>	> 1
<b>Solubility in Water:</b>	No data.
<b>Solubility Notes:</b>	Slightly soluble in water.
<b>Percent Volatile:</b>	No data.
<b>VOC / Volume:</b>	492.0000 G/L

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ] Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	No data available.
<b>Incompatibility - Materials To Avoid:</b>	Strong oxidizing agents, alkalis, acids, nitrates, metal salts and polymerization catalysts.
<b>Hazardous Decomposition Or Byproducts:</b>	Carbon monoxide, carbon dioxide, and various hydrocarbons and toxic vapors.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ] Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

## 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** Product has not been tested as a whole. Refer to section 2 for acute and chronic health effects.

CAS# 108-88-3:

Reproductive Effects:, TClO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Effects on Newborn: Behavioral.

- Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990

Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.

Result:

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Eye, ear.

- Prehled Prumyslove Toxikologie, Marhold, J., Organicke Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986

CAS# 100-41-4:

Tumorigenic Effects:, TClO, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 111-76-2:

Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.

Result:

Behavioral: Ataxia.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

## Bulldog Sealer &amp; Adhesion Promoter

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.

Result:

Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Musculoskeletal system.

- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.

Result:

Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.

Result:

Effects on Newborn: Apgar score (human only).

Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependency.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

**Carcinogenicity/Other Information:**

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

ACGIH A4 - Not Classifiable as a Human Carcinogen.

IARC 2B - Possibly Carcinogenic to Humans

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
540-88-5	Tert-Butyl acetate {Acetic acid, tert-butyl ester; Acetic acid, 1,1-dimethylethyl ester}	n.a.	n.a.	n.a.	n.a.
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	Possible	2B	A4	n.a.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	n.a.	3	A4	n.a.
108-38-3	m-Xylene {Benzene, m-Dimethyl-}	n.a.	n.a.	A4	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	n.a.	n.a.	A4	n.a.
106-42-3	p-Xylene {Benzene, p-Dimethyl-}	n.a.	n.a.	A4	n.a.
98-56-6	4-Chlorobenzotrifluoride {4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene}	n.a.	n.a.	n.a.	n.a.
79-20-9	Methyl acetate (Methyl ester of acetic acid)	n.a.	n.a.	n.a.	n.a.
110-43-0	2-Heptanone {Methyl pentyl ketone; n-Amyl methyl ketone}	n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	n.a.	n.a.	n.a.	n.a.
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	n.a.	n.a.	n.a.	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.



**SAFETY DATA SHEET**  
**Bulldog Sealer & Adhesion Promoter**

**12. ECOLOGICAL INFORMATION**

**General Ecological Information:** Product has not been tested as a whole.

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of in accordance with all applicable local, state, and federal regulations.

**14. TRANSPORT INFORMATION**

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Resin solution, [flammable]  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1866 **Packing Group:** II



**15. REGULATORY INFORMATION**

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
540-88-5	Tert-Butyl acetate {Acetic acid, tert-butyl ester; Acetic acid, 1,1-dimethylethyl ester}	No	Yes 5000 LB	No
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	No	Yes 1000 LB	Yes
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
108-38-3	m-Xylene {Benzene, m-Dimethyl-}	No	Yes 1000 LB	Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	No	Yes 1000 LB	Yes
106-42-3	p-Xylene {Benzene, p-Dimethyl-}	No	Yes 100 LB	Yes
98-56-6	4-Chlorobenzotrifluoride {4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene}	No	No	No
79-20-9	Methyl acetate (Methyl ester of acetic acid)	No	No	No
110-43-0	2-Heptanone {Methyl pentyl ketone; n-Amyl methyl ketone}	No	No	No
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	No	No	No
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230

**This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:**

[X] Yes [ ] No	Acute (immediate) Health Hazard
[X] Yes [ ] No	Chronic (delayed) Health Hazard
[X] Yes [ ] No	Fire Hazard
[ ] Yes [X] No	Sudden Release of Pressure Hazard
[ ] Yes [X] No	Reactive Hazard

# SAFETY DATA SHEET

## Bulldog Sealer & Adhesion Promoter

Page: 10

Printed: 05/04/2015

Revision: 05/04/2015

Supersedes Revision: 04/24/2008

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
540-88-5	Tert-Butyl acetate {Acetic acid, tert-butyl ester; Acetic acid, 1,1-dimethylethyl ester}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A PAIR; CA PROP.65: No
100-42-5	Styrene {Phenylethylene; Vinyl benzene; Styrol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes
108-38-3	m-Xylene {Benzene, m-Dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes
95-47-6	o-Xylene {Benzene, o-Dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
106-42-3	p-Xylene {Benzene, p-Dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: No
98-56-6	4-Chlorobenzotrifluoride {4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
79-20-9	Methyl acetate (Methyl ester of acetic acid)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: No
110-43-0	2-Heptanone {Methyl pentyl ketone; n-Amyl methyl ketone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
8052-41-3	Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
1321-74-0	Divinyl benzene (Benzene, Diethenyl-)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

### 16. OTHER INFORMATION

**Revision Date:** 05/04/2015

**Preparer Name:** W.M. Barr EHS Department (901)775-0100

**Additional Information About** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.