

# SAFETY DATA SHEET

## Goof Off Super Glue & Adhesive Remover

Page: 1 of 6

Printed: 04/13/2022

Revision: 09/11/2018

Supersedes Revision: 08/30/2018

This SDS complies with the Canadian Hazardous Products Regulations of 2015.

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Goof Off Super Glue & Adhesive Remover

**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113

**Phone Number:** (901)775-0100

**Web site address:** www.wmbarr.com

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Intended Use:** Removes super glue

**Product Code:** FG678

### 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2  
Serious Eye Damage/Eye Irritation, Category 2  
Carcinogenicity, Category 2  
Specific Target Organ Toxicity (single exposure), Category 3



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H225: Highly flammable liquid and vapor.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H351: Suspected of causing cancer.

**GHS Precautionary Phrases:** P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing gas/mist/vapors/spray.  
P264: Wash hands thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P235: Keep cool.

**GHS Response Phrases:** P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+313: IF exposed or concerned: Get medical attention/advice.  
P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
P337+313: If eye irritation persists, get medical advice/attention.  
P370+378: In case of fire, use dry chemical powder to extinguish.

# SAFETY DATA SHEET

## Goof Off Super Glue & Adhesive Remover

Page: 2 of 6

Printed: 04/13/2022

Revision: 09/11/2018

Supersedes Revision: 08/30/2018

**GHS Storage and Disposal Phrases:** P403+233: Store container tightly closed in well-ventilated place.  
P405: Store locked up.  
P501: Dispose of contents/container according to local, state and federal regulations.

**OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-64-1	Acetone {2-Propanone}	80.0 -100.0 %
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	10.0 -30.0 %

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:**

**Skin:**  
Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

**Eyes:**  
Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

**Inhalation:**  
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Ingestion:**  
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

**Signs and Symptoms Of Exposure:** Primary Routes of Exposure:  
Inhalation, ingestion, and dermal.

**Note to Physician:** Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

### 5. FIRE FIGHTING MEASURES

**Flash Pt:** Class IB  
-17.8 C (0.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Explosive Limits:** LEL: UEL:

**Autoignition Pt:**

**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, or alcohol-resistant foam.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

**Flammable Properties and Hazards:** Extremely Flammable!

Do not spread this product over a large surface area because the fire and health safety risks will increase dramatically.

# SAFETY DATA SHEET

## Goof Off Super Glue & Adhesive Remover

Page: 3 of 6

Printed: 04/13/2022

Revision: 09/11/2018

Supersedes Revision: 08/30/2018

**Flammability Classification:****Hazardous Combustion** carbon monoxide, carbon dioxide**Products:**

### 6. ACCIDENTAL RELEASE MEASURES

**Protective Precautions,  
Protective Equipment and  
Emergency Procedures:**

Vapors may cause flash fire or ignite explosively.

Safety glasses and chemical resistant gloves recommended.

**Environmental Precautions:**

Dispose in accordance with applicable local, state, and federal regulations.

**Steps To Be Taken In Case  
Material Is Released Or  
Spilled:**

Absorb the liquid and scrub the area with detergent and water.

### 7. HANDLING AND STORAGE

**Precautions To Be Taken in  
Handling:**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

**Precautions To Be Taken in  
Storing:**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or flame, furnace areas, pilot lights, stoves, etc. Do not reuse this container. Use product within one year of purchasing.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-64-1	Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	ACGIH TLV	TLV: 50 ppm STEL: 100 ppm	
		OSHA PELs	PEL: 200 ppm	

# SAFETY DATA SHEET

## Goof Off Super Glue & Adhesive Remover

<b>Respiratory Equipment (Specify Type):</b>	When used by the consumer following directions for use and with adequate ventilation, respiratory protection should not be needed.
<b>Eye Protection:</b>	Eye protection recommended
<b>Protective Gloves:</b>	Protective gloves recommended
<b>Other Protective Clothing:</b>	
<b>Engineering Controls (Ventilation etc.):</b>	Use with adequate ventilation.
<b>Work/Hygienic/Maintenance Practices:</b>	Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.  Do not eat, drink, or smoke in the work area.  Discard any clothing or other protective equipment that cannot be decontaminated.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ ] Gas [X] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Clear colorless thin liquid. Ketone odor.
<b>pH:</b>	
<b>Melting Point:</b>	
<b>Boiling Point:</b>	> 37.2 C (> 99.00 F)
<b>Flash Pt:</b>	-17.8 C (0.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)
<b>Evaporation Rate:</b>	> 1 (BuAC=1)
<b>Flammability (solid, gas):</b>	
<b>Explosive Limits:</b>	LEL: UEL:
<b>Vapor Pressure (vs. Air or mm Hg):</b>	185 MM HG at 20.0 C ( 68.0 F)
<b>Vapor Density (vs. Air = 1):</b>	> 1
<b>Specific Gravity (Water = 1):</b>	0.8025
<b>Density:</b>	0.8002 G/ML (6.677 - LB/GA)
<b>Solubility in Water:</b>	Miscible
<b>Octanol/Water Partition Coefficient:</b>	
<b>Percent Volatile:</b>	100.0 % by weight.
<b>VOC / Volume:</b>	15.0000 % WT
<b>Autoignition Pt:</b>	
<b>Decomposition Temperature:</b>	
<b>Viscosity:</b>	

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ] Stable [X]
<b>Conditions To Avoid - Instability:</b>	
<b>Incompatibility - Materials To Avoid:</b>	Avoid contact with acids, aldehydes, alkalies, amines, ammonia, oxidizing agents, reducing agents, chlorine compounds.  May form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers.
<b>Hazardous Decomposition or</b>	Decomposition may produce carbon monoxide, carbon dioxide, nitrogen oxides, and

# SAFETY DATA SHEET

## Goof Off Super Glue & Adhesive Remover

Page: 5 of 6

Printed: 04/13/2022

Revision: 09/11/2018

Supersedes Revision: 08/30/2018

**Byproducts:** other asphyxiants.  
**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]  
**Conditions To Avoid - Hazardous Reactions:**

### 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** This product has not been tested as a whole. Information below will be for individual ingredients. Refer to section 2 for acute and chronic health effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 109-99-9:

Other Studies:, TDLo, Oral, Rat, 26280. mg/kg.

Result:

Liver: Tumors.

Kidney, Ureter, Bladder: Kidney tumors.

- Toxicologist., Soc. of Toxicology, Inc., 475 Wolf Ledge Parkway, Akron, OH 44311, Vol/p/yr: 60,286, 2001

**Carcinogenicity/Other Information:** ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}			A4	
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}				

### 12. ECOLOGICAL INFORMATION

**General Ecological Information:** This product has not been tested as a whole.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with local, state, and federal laws.

### 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Acetone solution

**DOT Hazard Class:** 3 FLAMMABLE LIQUID

**UN/NA Number:** UN1090

**Packing Group:** II



## Goof Off Super Glue &amp; Adhesive Remover

Printed: 04/13/2022

Revision: 09/11/2018

Supersedes Revision: 08/30/2018

## LAND TRANSPORT (Canadian TDG):

## TDG Shipping Name:

UN Number: 1090 Packing Group: II

Hazard Class: 3 - FLAMMABLE LIQUID TDG Classification:

## Additional Transport Information:

The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

## EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes NA	No
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	No	Yes NA	No

CAS #	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
67-64-1	Acetone {2-Propanone}	No	No	Yes
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	Yes: Part 5	No	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	TSCA: Inventory
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	TSCA: Inventory, 8A PAIR CA PROP.65: Yes: Canc.

## Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

## 16. OTHER INFORMATION

Revision Date:	09/11/2018	Previous revision:	08/30/2018
Preparer Name:	W.M. Barr EHS Department (901)775-0100		

## Additional Information About

## This Product:

## Company Policy or

## Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.