

1 Identification

- **Product identifier**
- **Trade name:** M25611 Griptide Sail White
- **Article number:** M25611
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

- **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

USA

Trade name: M25611 Griptide Sail White

(Contd. of page 1)

- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 0 | Health = 0 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

| | | |
|------------|--------------------|----------|
| 123-86-4 | n-butyl acetate | 10-13% |
| 540-88-5 | tert-butyl acetate | 5-7% |
| 110-43-0 | heptan-2-one | 1.5-5% |
| 25053-09-2 | Acrylic Polymer | 1.5-5% |
| 1330-20-7 | xylene | 1-1.5% |
| 67-64-1 | acetone | 1-1.5% |
| 108-88-3 | toluene | ≥0.1-≤1% |
| 100-41-4 | ethylbenzene | ≥0.1-≤1% |

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



Trade name: M25611 Griptide Sail White

(Contd. of page 2)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-------------|---------------------------------|-------------------------|
| 123-86-4 | n-butyl acetate | 5 ppm |
| 13463-67-7 | titanium dioxide | 30 mg/m ³ |
| 540-88-5 | tert-butyl acetate | 600 ppm |
| 110-43-0 | heptan-2-one | 150 ppm |
| 1330-20-7 | xylene | 130 ppm |
| 67-64-1 | acetone | 200 ppm |
| 108-88-3 | toluene | 67 ppm |
| 112945-52-5 | SILICA | 18 mg/m ³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| 78-93-3 | butanone | 200 ppm |
| 100-41-4 | ethylbenzene | 33 ppm |
| 77-58-7 | dibutyltin dilaurate | 1.1 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 0.075 mg/m ³ |

(Contd. on page 4)



Trade name: M25611 Griptide Sail White

(Contd. of page 3)

| | | |
|------------|--------------------------|--------|
| 108-83-8 | 2,6-dimethylheptan-4-one | 75 ppm |
| 70657-70-4 | 2-methoxypropyl acetate | 50 ppm |

· PAC-2:

| | | |
|-------------|---------------------------------|-----------------------|
| 123-86-4 | n-butyl acetate | 200 ppm |
| 13463-67-7 | titanium dioxide | 330 mg/m ³ |
| 540-88-5 | tert-butyl acetate | 1,700 ppm |
| 110-43-0 | heptan-2-one | 670 ppm |
| 1330-20-7 | xylene | 920* ppm |
| 67-64-1 | acetone | 3200* ppm |
| 108-88-3 | toluene | 560 ppm |
| 112945-52-5 | SILICA | 100 mg/m ³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 78-93-3 | butanone | 2700* ppm |
| 100-41-4 | ethylbenzene | 1100* ppm |
| 77-58-7 | dibutyltin dilaurate | 8 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 33 mg/m ³ |
| 108-83-8 | 2,6-dimethylheptan-4-one | 330 ppm |
| 70657-70-4 | 2-methoxypropyl acetate | 1,000 ppm |

· PAC-3:

| | | |
|-------------|---------------------------------|-------------------------|
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 13463-67-7 | titanium dioxide | 2,000 mg/m ³ |
| 540-88-5 | tert-butyl acetate | 10,000 ppm |
| 110-43-0 | heptan-2-one | 4000* ppm |
| 1330-20-7 | xylene | 2500* ppm |
| 67-64-1 | acetone | 5700* ppm |
| 108-88-3 | toluene | 3700* ppm |
| 112945-52-5 | SILICA | 630 mg/m ³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 78-93-3 | butanone | 4000* ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 77-58-7 | dibutyltin dilaurate | 48 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 200 mg/m ³ |
| 108-83-8 | 2,6-dimethylheptan-4-one | 2000* ppm |
| 70657-70-4 | 2-methoxypropyl acetate | 5,000 ppm |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 5)



Trade name: M25611 Griptide Sail White

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate

| | |
|-----|--|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Long-term value: 950 mg/m ³ , 200 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |

540-88-5 tert-butyl acetate

| | |
|-----|--|
| PEL | Long-term value: 950 mg/m ³ , 200 ppm |
| REL | Long-term value: 950 mg/m ³ , 200 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |

110-43-0 heptan-2-one

| | |
|-----|--|
| PEL | Long-term value: 465 mg/m ³ , 100 ppm |
| REL | Long-term value: 465 mg/m ³ , 100 ppm |
| TLV | Long-term value: 233 mg/m ³ , 50 ppm |

1330-20-7 xylene

| | |
|-----|--|
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI |

67-64-1 acetone

| | |
|-----|---|
| PEL | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV | Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI |

(Contd. on page 6)



Trade name: M25611 Griptide Sail White

(Contd. of page 5)

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

67-64-1 acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 7)

Trade name: M25611 Griptide Sail White

(Contd. of page 6)

100-41-4 ethylbenzene

| | |
|-----|---|
| BEI | 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| - | Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) |

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

| | |
|--------|--------|
| Form: | Liquid |
| Color: | White |
- **Odor:** Characteristic
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

| | |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
|------------------------------|---------------|

(Contd. on page 8)



Trade name: M25611 Griptide Sail White

(Contd. of page 7)

| | |
|---|--|
| Boiling point/Boiling range: | 97 °C |
| · Flash point: | 15 °C |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 370 °C |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
| · Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 °C: | 10.7 hPa |
| · Density at 20 °C: | 1.21421 g/cm ³ |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 23.2 % |
| Water: | 0.1 % |
| VOC content: | 16.27 % |
| | 201.6 g/l / 1.68 lb/gl |
| Solids content: | 76.8 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 9)



Trade name: M25611 Griptide Sail White

(Contd. of page 8)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|------------|----------------------------|----|
| 13463-67-7 | titanium dioxide | 2B |
| 1330-20-7 | xylene | 3 |
| 108-88-3 | toluene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| 14808-60-7 | Quartz (SiO ₂) | 1 |

- **NTP (National Toxicology Program)**

| | | |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO ₂) | K |
|------------|----------------------------|---|

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



(Contd. on page 10)

Trade name: M25611 Griptide Sail White

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|---|---|
| · UN-Number · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name · DOT · ADR · IMDG, IATA | Paint 1263 Paint, special provision 640D PAINT |
| · Transport hazard class(es) · DOT | |
|  | |
| · Class · Label | 3 Flammable liquids 3 |
| · ADR, IMDG, IATA | |
|  | |
| · Class · Label | 3 Flammable liquids 3 |
| · Packing group · DOT, ADR, IMDG, IATA | II |
| · Environmental hazards: · Marine pollutant: | No |
| · Special precautions for user · EMS Number: · Stowage Category | Warning: Flammable liquids F-E, S-E B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: · DOT · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| · ADR · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |

(Contd. on page 11)



Trade name: M25611 Griptide Sail White

(Contd. of page 10)

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

| | |
|-----------|---------------|
| | Acrylic Resin |
| 1330-20-7 | xylene |
| 108-88-3 | toluene |
| 78-93-3 | butanone |
| 100-41-4 | ethylbenzene |

· **TSCA (Toxic Substances Control Act):**

| | |
|------------|---|
| 1317-65-3 | GROUND CALCIUM CARBONATE |
| 66070-58-4 | Styrene-Ethylene/Butylene-Styrene block Copolymer |
| 123-86-4 | n-butyl acetate |
| 13463-67-7 | titanium dioxide |
| 540-88-5 | tert-butyl acetate |
| 110-43-0 | heptan-2-one |
| 25053-09-2 | Acrylic Polymer |
| 1330-20-7 | xylene |
| 67-64-1 | acetone |
| 108-88-3 | toluene |
| 108-65-6 | 2-methoxy-1-methylethyl acetate |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. |
| 78-93-3 | butanone |
| 100-41-4 | ethylbenzene |
| 61791-55-7 | Amines, N-tallow alkyltrimethylenedi- |
| 77-58-7 | dibutyltin dilaurate |
| 14808-60-7 | Quartz (SiO ₂) |
| 9038-95-3 | OXIRANE,ME, POLYMER |
| 19549-80-5 | 4,6-dimethylheptan-2-one |
| 108-83-8 | 2,6-dimethylheptan-4-one |
| 7732-18-5 | water |

(Contd. on page 12)

Trade name: M25611 Griptide Sail White

(Contd. of page 11)

· **TSCA new (21st Century Act) (Substances not listed)**

25053-09-2 Acrylic Polymer

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

1330-20-7 xylene

100-41-4 ethylbenzene

14808-60-7 Quartz (SiO₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

67-64-1 acetone

I

108-88-3 toluene

II

78-93-3 butanone

I

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7 titanium dioxide

A4

1330-20-7 xylene

A4

67-64-1 acetone

A4

108-88-3 toluene

A4

100-41-4 ethylbenzene

A3

77-58-7 dibutyltin dilaurate

A4

14808-60-7 Quartz (SiO₂)

A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO₂)

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H351 Suspected of causing cancer.

(Contd. on page 13)

Trade name: M25611 Griptide Sail White

(Contd. of page 12)

H361 Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 03/14/2018 / 12

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

· *** Data compared to the previous version altered.**