

# SAFETY DATA SHEET

### SECTION 1 | MATERIAL AND MANUFACTURER IDENTIFICATION

#### PRODUCT

Product Identifier: OS-1 Intended Product Use: Odor, Stain & Soil Remover Manufacturer Identification Code: 2175, 2175C

#### MANUFACTURER

Chemical Technologies International Inc. P.O. Box 968 Rancho Cordova, CA 95741 USA Phone: (916) 638-1315 Fax: (916) 638-0712 24 hours Emergency Assistance Calls (USA): CHEMTREC (800) 424-9300 Please reference name and manufacturers identification number

### SECTION 2 | HAZARD(S) INDENTIFICATION

#### **GHS CLASSIFICATION**

Oxidizing liquids (Category 3) Acute toxicity, Oral (Category 4) Skin irritation (Category 2) Skin sensitization (Category 1) Eye irritation (Category 2B) Acute toxicity, Inhalation (Category 5)

Routes of Exposure: Eye contact, skin contact, inhalation, and ingestion.

**Inhalation:** Inhalation of mist or vapor may cause severe irritation of the respiratory tract that usually subsides after exposure ceases.

**Eye Contact:** Vapors may irritate eyes. Direct or prolonged contact with eyes will be painful and irritating may also cause possible permanent damage. Seek immediate medical attention for prolonged irritation.

**Skin Contact:** Repeated exposure may cause skin irritation, drying, chapping.

**Ingestion:** If swallowed will cause irritation/corrosion of the gastrointestinal tract. Seek immediate medical attention. **Carcinogenic Potential:** Not established

Acute Effects: This product is considered to be a potential irritant. This product should not be used for any other purpose than the intended use in section 1.

Chronic Effects: Not established.



Health hazard	1
Flammability hazard	0
Reactivity hazard	1
Other hazard	OX



Signal word: Warı	ning
Hazard statement	s): H272: May intensify fire; oxidizer.
	H302: Harmful if swallowed;
	H315: Causes mild skin irritation.
	H317: May cause an allergic skin reaction.
	H320: Causes eye irritation.
	H333: May be harmful if inhaled
SECTION 3	COMPOSITON/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	CONCENTRATIONS
1. Hydrogen Peroxide	7722-84-1	20-40%
2. Acrylate Copolymer	Not Established	1-10%
3. 2-Butoxyethanol	111-76-2	1-10%

This SDS contains confidential and propriety information of CTI and is protected by copyright, trade secret and other State and Federal laws. Its receipt or possession does not convey any rights to reproduce its contents, or to manufacture, use or anything it may describe. Reproduction, disclosure, or use without specific written authorization of CTI is strictly forbidden.

# SECTION 4 FIRST-AID MEASURES

**Inhalation:** Remove from further exposure to fresh air. If respiratory irritation, dizziness, or nausea occurs seek immediate medical attention.

**Eye Contact:** Flush eyes with a directed stream of water for 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Washing eyes immediately after exposure is essential to achieve maximum effectiveness and minimize potential irritation. If irritation persists, seek immediate medical attention.

Skin Contact: Wash contact areas with soap and water. Launder exposed clothing before reuse.

Ingestion: If swallowed, do not induce vomiting. Seek immediate medical attention.

# SECTION 5 FIRE-FIGHTING MEASURES

#### FLAMMABILITY PROPERTIES

*Flashpoint*: Non-flammable nor combustible *Flammable Limits*: Not Available *Auto ignition Temperature*: Not Available

#### FIREFIGHTING PROCEDURES

*General Hazard*: During a fire smoke may contain the original material in addition to toxic and or irritating compounds. Avoid heat sparks or open flame. Oxidizer property of this mixture will increase the burning rate of combustible materials and may intensify the fire.

Firefighting Instructions: Evacuate all unnecessary personnel. Use water, foam, dry chemical or CO<sub>2</sub>.

*Firefighting Equipment*: Firefighters should wear NICSH/MSHA approved self-contained, positive pressure breathing apparatus and full protective clothing.

Hazardous Combustion Products: During fire, smoke may contain the original material in addition to toxic and/or irritating compounds such as but not limited to: Carbon oxides, sodium oxides, silicon oxides Unusual Fire and Explosion Hazards: Not established



## SECTION 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Persons performing the cleanup should wear personal protective equipment sufficient to keep material away from skin. Avoid direct contact with material. See section 4 for First-Aid Advice. See section 5 for Firefighting Advice.

#### **PROTECTIVE MEASURES**

To minimize exposure to all chemicals, including this product, use good industrial hygiene and common sense. Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (See section 4 for more advice). Wear NIOSH/MSHA approved organic respirator when ventilation is not adequate or when the sufficiency of ventilation to maintain concentrations below exposure limits is in question. Wear chemical safety goggles to protect against splashes or contact with eyes. See OSHA 29 CFR 1910.33

#### **CLEAN-UP PROCEDURES**

*Small Spills*: Wipe up or mop to dispose of spill in DOT approved waste container.

*Large Spills*: Contain by diking with soil or other non-combustible absorbent material, and dispose into DOT approved waste container. If possible complete clean up on a dry basis. Comply with all applicable governmental regulations on spill reporting, handling and disposal of waste. Contain all spills or leaks to prevent discharge into the environment. Responsibility of all spills or releases reported to the appropriate local, state and federal agencies falls upon the user.

# SECTION 7 HANDLING AND STORAGE

#### HANDLING

This product is professional strength product to be used by professionals only. Avoid breathing vapors/mist of this product. Always keep container tightly closed and properly labels. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Impervious boots/shoes covering should be used if material is anticipated to contact feet. As with all chemicals, practice good industrial hygiene when handling this product. Always work in a well-ventilated area and avoid inhalation of product vapor or mist. Do not ingest.

The manufacturer and seller warrant that this product conforms to its standard specifications when used according to directions. As the conditions of method of its use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true but all statements and suggestions are made without any warranty, expressed or implied, regarding accuracy of the information. The hazards connected with the use of this material and the results to be obtained from the use thereof.

#### STORAGE

Avoid excessive heat. Avoid storage with oxidizing or reducing agents and/or acids. Employees should be trained to handle this product safely. Store the product in a cool dry area away from ignition sources. Loosen closures cautiously. Avoid storage with combustible organic materials.

*Storage temperature*: Store in cool dry place *Storage pressure*: Atmospheric



# SECTION 8 EXPOSURE / PERSONAL PROTECTION

#### **EXPOSURE LIMITS**

Exposure limits have not been established for this mixture. Avoid, as far as reasonably practicable, inhalation of vapor, mists or fumes generated. Limits for components are listed below:

COMPONENT #	OSHA PEL TWA STEL	ACGIH TLV TWA STEL	NIOSH TWA STEL
1. Hydrogen Peroxide	1 ppm	1 ppm	1 ppm
2. Acrylate Copolymer	Not Established	Not Established	Not Established
3. 2-Butoxyethanol	50ppm	20ppm	5ppm, 240mg/m3

#### **ENGINEERING CONTROLS**

The level of protection and types of control will vary depending upon potential exposure conditions. If user operations generate dust, fume or mist, use adequate ventilation to keep exposure below exposure limit.

#### PERSONAL PROTECTION

*Ventilation and engineering controls*: Use only in well ventilated area. If necessary, use exhaust ventilation to insure adequate ventilation. Insure that water is readily available and that you are prepared to properly wash out your eyes should the need arise. (Refer to section 4).

*Respiratory:* Wear NIOSH/MSHA approved respirator when ventilation is not adequate. A NIOSH /MSHA –approved air purifying respirator with an organic vapor cartridge or canister may be advisable under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure, air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Eye Protection: Wear safety goggles to protect against eye contact. See OSHA 29 CFR 1910.33

*Skin:* Wear chemical impervious gloves. Wear protective clothing to minimize skin contact. Wash skin after use. Wash contaminated clothing and dry before reuse.

*Other:* One should always use chemicals with an awareness of the potential hazard of the effect on the human system. To minimize employee exposure to all chemicals, including this product, use good industrial hygiene practices.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Liquid Odor: Light Odor Vapor density: Not Available. Freezing point: Not Available. Solubility in water: Soluble Flammability: Not Flammable Viscosity: Not Available. Flash point: Non-Flammable, Noncombustible Evaporation rate: Not Available. Vapor pressure: Not Available. Color: Clear pH: 6.5 Boiling point: Not Available. Melting point: Not Available. Density: Not Available. Evaporation rate: Not Available. Vapor density: Not Available. Relative density: Not Available. Flammability (solid, gas): Not Applicable. Vapor density: Not Available.



# SECTION 10 STABILITY AND REACTIVITY

*Chemical Stability:* Unstable under ambient temperature and atmospheric pressure.

*Conditions to avoid:* Keep away from heat or excessive pressure. Keep away from heat or excessive pressure. Do not contaminate.

Incompatibility with other materials: Heavy metals, combustible organic materials, reducing agents.

*Hazardous decomposition products:* Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Sulfur oxides.

Hazardous polymerization: Major components of this mixture show no hazardous polymerization.

Conditions to Avoid: Oxygen, which supports combustion.

### SECTION 11 TOXICOLOGICAL INFORMATION

Toxicological information has not been established on this mixture. Toxicological information on components within this mixture is given by:

COMPONENT #	ΤΟΧΙΟΙΤΥ
1. Hydrogen Peroxide	Not Established
2. Acrylate Copolymer	Not determined. Similar products tested for $LD_{50}$ limit value are greater than 10,000
mg / KG.	
<ol><li>2-Butoxyethanol</li></ol>	LD <sub>50</sub> Oral - mouse - 470 mg/kg, rat 1230mg/kg
	LD50 Dermal - rabbit - 220 mg/kg

# SECTION 12 ECOLOGICAL INFORMATION

Ecological information has not been established for this product. Ecological information on components within this mixture is given by:

COMPONENT #	TOXICITY
1. Hydrogen Peroxide	Not Established
2. Acrylate Copolymer	Not Established
3. 2-Butoxyethanol	Not Established
2. Acrylate Copolymer	Not Established

# SECTION 13 DISPOSAL CONSIDERATIONS

Dispose of all waste, empty bottles and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations.

Do not dump into storm drains or any body of water. All disposal methods must be in compliance with all federal, State/ Province and local laws and regulations. Regulations may vary in different locations.

Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. The vendor has no control over the management practices or the processes by which the party who handles or uses this material. The information presented here pertains only to the product as shipped in its intended condition and recommended usage.



### SECTION 14 TRANSPORT INFORMATION

#### DOT (US):

These shipments are ORM-D and exempt from Bill of Lading requirements when sent via ground under 1 Liter when packaged for retail sale per 49 CFR 173.152. If product exceeds 1 Liter then will comply with the following:

UN Number: 3139 Proper Shipping Name: Oxidizing Liquid n.o.s. (Contains Hydrogen Peroxide) Hazard Class: 5.1 Labels: Oxidizer Packaging Group: III

#### IMDG:

Basic Description: <u>UN3139</u>, <u>Oxidizing Liquid n.o.s.</u> (Contains Hydrogen Peroxide), 5.1, III, LTD QTY Marine Pollutant: No

\*Shipping Instructions as shipped are: ORMD/LTD QTY Exemptions Used 173.152 LTD QTY & ORM-D Consult 49 CFR to assure compliance with all applicable federal, state/provincial and local laws and regulations that may apply to you.

SECTION 15	REGULARTORY INFORMATION

US Federal Regulations:

OSHA standards require that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheet (SDS) sheets, training and access to written records. We request that you, as per your legal duty to, make all information in this SDS available to your employees and those who handle or consume the product To aid our customers in complying with regulatory requirements regulatory information for components of this product are indicated below

This *mixture* has *no established regulatory information* all regulatory information given is based on individual components of the mixture by component number

<b>COMPONENT #</b> 1. Hydrogen Peroxide	HAZARD OSHA Hazards: Oxidizer, Target Organ Effect, Toxic by ingestion, Corrosive, Carcinogen SARA 302 Components: Hydrogen peroxide; CAS-No.7722-84-1 SARA 311/312 Hazards: Reactivity Hazard, Acute & Chronic Health Hazard MA, PA & NJ Right To Know Components: Hydrogen peroxide; CAS.7722-84-1
2. Acrylate Copolymer 3. 2-Butoxyethanol	Not Established OSHA Hazards: Combustible Liquid, Target Organ Effect, Harmful by ingestion., Harmful by skin absorption., Irritant, Carcinogen SARA 313 Components: :2-Butoxyethanol CAS-No.111-76-2 SARA 311/312 Hazards: Fire Hazard, Acute Health Hazard, Chronic Health Hazard



## SECTION 16 OTHER INFORMATION

While the information is believed to be accurate, CTI makes no representations as to its accuracy or sufficiency. This SDS summarizes to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources of each individual component. Since CTI cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. Users are responsible to verify this data under their own operating conditions to determine whether this product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance on information contained herein. This information relates only to the product-designated herein, and does not relate to its use in combination with any other material or in any other process.