

# Temperature & Humidity Sensor

Featuring LoRaWAN®

EM300-TH

*Milesight*



EM300-TH is a compact environment monitoring sensor for measurement of temperature and humidity and transmitting data using LoRaWAN® technology. With this low power consumption technology, EM300-TH can work up to 5 years with 4000 mAh battery. Combining with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, users can manage all sensor data remotely and visually.

EM300-TH is widely used for both indoor and outdoor applications such as offices, hospitals, factories, greenhouses, etc.

## ◆ Features

- Embedded with Sensirion high-precision sensor chip
- Ultra-wide-distance transmission up to line of sight of 10km
- IP67 UV-resistant and waterproof enclosure for harsh environment applications
- Built-in 4000 mAh replaceable battery and works for more than 5 years without replacement
- Store locally 3,000 historical records and support retransmission to prevent data loss
- Support Milesight D2D protocol to enable ultra-low latency and direct control without gateways
- Equipped with NFC for easily configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud solution

## ◆ Specifications

<b>Wireless Transmission</b>	
Technology	LoRaWAN®, Milesight D2D
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4
Tx Power	16dBm(868 MHz)/20dBm(915 MHz)/19dBm(470 MHz)
Sensitivity	-137dBm @300bps
Mode	OTAA/ABP Class A
<b>Measurement</b>	
<b>Temperature</b>	
Range	-30°C to + 70°C
Accuracy	0°C to + 70°C (+/- 0.3°C), -30°C to 0°C (+/- 0.6°C)
Resolution	0.1°C
<b>Humidity</b>	
Range	0% to 100% RH
Accuracy	10% to 90% RH (+/- 3%), below 10% and above 90% RH (+/- 5%)
Resolution	0.5% RH
<b>Operation</b>	
Power On & Off	NFC, Power Button (Internal)
Configuration	NFC Configuration via Mobile App
Advanced Feature	Milesight D2D Controller, Data Storage, Data Retransmission
<b>Physical Characteristics</b>	
Power Supply	1 × 4000 mAh ER18505 Li-SOCL <sub>2</sub> Battery (extendable to 2 batteries)
Battery Life*	10 years (10 min interval)
Operating Temperature	-30°C to +70°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	IP67
Dimension	88.5 × 85.3 × 27 mm (3.48 × 3.36 × 1.06 in)
Installation	Wall Mounting
<b>Approvals</b>	
Regulatory	CE, FCC
Environmental	RoHS

\* Tested under laboratory conditions and for guideline purposes only.

