

| | | | | | | Parkett will das Deste: |
|------------------------------|---|---|---|---|-------------------------------------|-------------------------|
| Article Print o Versio | date: 25. | 14000AAJ10 02.2023 000 | AquaSeal FlexPrim Revision date: 25.0 Issue date: 05.11.2 |)2.2023 | 56142 US Page 1 / 7 | |
| SEC | TION 1: Identif | ication of the | substance/mixtu | ire and of the o | company/undertaking | |
| 1.1. | Product identif | ier | | | | |
| | Article No. (man Trade name/des | | ier) | XG14000AAJ1 AquaSeal Flex Stat.Warennun | | |
| 1.2. | | | e substance or mix | cture and uses a | advised against | |
| | Relevant identi paint and/or pain Uses advised a Do not use for ir Product is not in | nt related mater gainst njecting or spray | /ing. | | | |
| 1.3. | | | safety data sheet | | | |
| | supplier (manu Berger-Seidle G Parkettlacke - K Maybachstraße 67269 Grünstad Germany Department res | f acturer/impor mbH lebstoffe - Bauc 2 t | ter/downstream us | - | 9 6359 / 8005-0 359 / 8005-170 | |
| | Laboratory E-mail | | | Sicharbaitedate | en@berger-seidle.de | |
| 1.4. | Emergency tele | - | | | 9 700 24112112 (BLG) | |
| SEC | TION 2: Hazard | ls identificati | on | | | |
| 2.1. 2.2. | Classification of GHS-US classification | fication | ce or mixture | | | |
| <u></u> | GHS-US labelin | | | | | |
| | Hazard pictogra | _ | | | | |
| | Hazard stateme | ents not appli | cable | | | |
| | Precautionary | not appli | | | | |
| | Hazard compo | nents for label | ling | | | |
| 2.3. | Other hazards No information a | available. | | | | |
| | Other informati If medical advid use. | | nave product conta | iner or label at h | nand. Keep out of reach of childr | en. Read label before |
| SEC | TION 3: Compo | osition/inforn | nation on ingredie | ents | | |
| 3.2. | Mixtures | | | | | |
| | Description | | ased surface finishes | s, solvent conten | t up to 5%, N-methylpyrrolidone-fre | e |
| | Hazardous ingredients | | | | | |
| | GHS-US classif | tication | | | | |
| | CAS No. | Designa // Remai | | | | weight-% |



| Article No.: | XG14000AAJ10 | AquaSeal FlexPrimer |
|--------------|--------------|---------------------------|
| Print date: | 25.02.2023 | Revision date: 25.02.2023 |
| Version: | 5.0000 | Issue date: 05.11.2022 |

56142 US Page 2 / 7

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof



| Article No.: | XG14000AAJ10 | AquaSeal FlexPrimer | |
|--------------|--------------|---------------------------|------------|
| Print date: | 25.02.2023 | Revision date: 25.02.2023 | 56142 US |
| Version: | 5.0000 | Issue date: 05.11.2022 | Page 3 / 7 |

tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



| Article Print d Versio | ate: | XG14000AAJ10 25.02.2023 5.0000 | AquaSeal FlexP Revision date: 2 Issue date: 05.1 | 5.02.2023 | 56142 US Page 4 / 7 |
|------------------------------|---|--|--|--|--|
| | Physical s Colour: | tate: | | Liquid white | |
| | Odour: | | | characteristic | |
| | Odour three | eshold: | | not applicable | |
| | Initial boili | ng point and boilin | ig range: | 100 °C Source: Water | |
| | | upper explosion li | mit: | | |
| | | plosion limit: plosion limit: | | not applicable not applicable | |
| | Flash poin | - | | not applicable | |
| | - | on temperature: | | not applicable | |
| | - | sition temperature: | | not applicable | |
| | pH at 20 °C | D: | | 8 - 8,3 / 100,0 weight | t-% |
| | Cinematic | viscosity (40°C): | | < 135 mm²/s | |
| | Viscosity a | at 20 °C: | | 25 s 4 mm Method: DIN 53211 | |
| | Solubility(Water sol | ies): ubility at 20 °C: | | miscible | |
| | Partition c | oefficient: n-octan | ol/water: | see section 12 | |
| | Vapour pro | essure at 20 °C: | | 23 mbar Method: calculated. Source: Water | |
| | Density an Density at | d/or relative densit 20 °C: | iy: | 1,02 g/cm³ Method: ISO 2811, p | art 3 |
| | Relative va | apour density: | | not applicable | |
| | particle ch | aracteristics: | | not applicable | |
| 9.2. | Other info | rmation | | | |
| | Solvent se | paration test: | | < 3 weight-% (ADR/F | RID) |
| SEC | TION 10: S | tability and react | ivity | | |
| 10.1. | Reactivity No informa | tion available. | | | |
| 10.2. | Chemical stability Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. | | | | |
| 10.3. | - | of hazardous reac from strong acids, s | | strong oxidizing agents | s to avoid exothermic reactions. |
| 10.4. | Conditions Stable whe | s to avoid in applying the recor | nmended regulati | ons for storage and ha | andling. Further information on correct storage: refer to re to high temperatures. |
| 10.5. | | ble materials | | • | |
| 10.6. | Hazardous Hazardous | decomposition pr | | with exposure to high | temperatures, e.g.: carbon dioxide, carbon monoxide, |
| SEC | TION <u>1</u> 1: T | oxicological info | rmation | | |
| 11.1. | | | es as defined in F | Regulation (EC) No 12 | 72/2008 |
| | Acute toxi Based on a | city available data, the cl | assification criteri | a are not met. | |



| Article No.: | XG14000AAJ10 | AquaSeal FlexPrimer |
|--------------|--------------|---------------------------|
| Print date: | 25.02.2023 | Revision date: 25.02.2023 |
| Version: | 5.0000 | lssue date: 05.11.2022 |

56142 US Page 5 / 7

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product



| Article No.: Print date: | XG14000AAJ10 25.02.2023 5.0000 | AquaSeal FlexPrimer Revision date: 25.02.2023 | 56142 US |
|-----------------------------|--------------------------------------|--|------------|
| Version: | 5.0000 | Issue date: 05.11.2022 | Page 6 / 7 |

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

| | No dangerous good in sense of this transpor | t regulation. |
|-------|--|--|
| 14.1. | UN number or ID number | |
| | | not applicable |
| 14.2. | UN proper shipping name | |
| 14.3 | Transport hazard class(es) | |
| | | not applicable |
| 14.4. | Packing group | |
| | | not applicable |
| 14.5. | Environmental hazards | |
| | Land transport (ADR/RID) | not applicable |
| | Marine pollutant | not applicable |
| 14.6. | Special precautions for user | |
| | Transport always in closed, upright and safe cor case of an accident or leakage. Advices on safe handling: see parts 6 - 8 | ntainers. Make sure that persons transporting the product know what to do in |
| | Further information | |
| | Land transport (ADR/RID) | |
| | Tunnel restriction code | - |
| | Sea transport (IMDG) | |
| | EmS-No. | not applicable |
| 14.7. | Maritime transport in bulk according to IMO i | nstruments |
| | | |

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal regulations

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 50

VOC-value (in g/L) ASTM D2369: 149

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 140 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 50

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA



| Article No.: | XG14000AAJ10 | AquaSeal FlexPrimer | |
|--------------|--------------|---------------------------|------------|
| Print date: | 25.02.2023 | Revision date: 25.02.2023 | 56142 US |
| Version: | 5.0000 | lssue date: 05.11.2022 | Page 7 / 7 |

Inventory exemption

15.2. Chemical Safety Assessment

SECTION 16: Other information

Chemical safety assessments for substances in this mixture were not carried out.

Abbreviations and acronyms ADR European Agreement concerning the International Carriage of Dangerous Goods by Road OEL Occupational Exposure Limit Value BLV **Biological Limit Value** Chemical Abstracts Service CAS Classification, Labelling and Packaging CLP Carcinogenic, Mutagenic and Reprotoxic CMR German Institute for Standardization / German industrial standard DIN DNEL Derived No-Effect Level European Waste Catalogue Directive EAKV EC Effective Concentration EC **European Community** ΕN European Standard IATA-DGR International Air Transport Association - Dangerous Goods Regulations International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IBC Code ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization LC Lethal Concentration LD Lethal Dose MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD Organisation for Economic Cooperation and Development PBT persistent, bioaccumulative, toxic PNEC Predicted No Effect Concentration REACH Registration, Evaluation, Authorisation and Restriction of Chemicals RID Regulations concerning the International Carriage of Dangerous Goods by Rail UN **United Nations** Volatile Organic Compounds VOC vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.