



LUMIX S PRO 24-70mm F2.8 (S-E2470) L-Mount Lens
Standard Zoom Lens

Features

Lens Construction	18 elements in 16 groups (3 aspherical lenses, 4 ED lenses, 1 UHR lens)
Mount	L-Mount
Optical Image Stabilizer	No
Focal Length	f=24-70mm
Aperture Type	11 diaphragm blades / Circular aperture diaphragm
Maximum Aperture	F2.8
Minimum Aperture	F22
Closest Focusing Distance	0.37m / 1.21ft
Maximum Magnification	Approx. 0.25x

General

Diagonal Angle of View	84°(Wide) - 34°(Tele)
Dust and Splash Resistant	Yes*
Recommended Operating Temperature	-10oC to 40oC (14oF to 104oF)
Filter Size	φ82mm
Max. Diameter	φ90.9mm / 3.58inch
Overall Length	Approx. 140mm / 5.51inch (from the tip of the lens to the base side of the lens mount)

Weight

Approx. 935g / 32.98oz (excluding lens cap, lens rear cap and lens hood)

Standard Accessories

Lens cap, Lens rear cap, Lens hood, Lens storage bag

NOTE

NOTE

*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

All specifications are subject to change without notice.

© Panasonic