## **Panasonic**





## LUMIX S PRO 70-200mm F2.8 O.I.S. (S-E70200) L-Mount Lens Telephoto Zoom Lens

## Name **Lens Construction** 22 elements in 17 groups (1 aspherical lens, 3 ED lenses, 2 UED lenses) Mount L-Mount **Optical Image Stabilizer** Yes **Focal Length** f=70-200mm 11 diaphragm blades / Circular aperture diaphragm **Aperture Type Maximum Aperture** F2.8 F22 **Minimum Aperture Closest Focusing Distance** 0.95m / 3.12ft **Maximum Magnification** Approx. 0.21x General **Diagonal Angle of View** 34°(Wide) - 12°(Tele) **Dust and Splash Resistant** Yes\* **Recommended Operating** -10oC to 40oC (14oF to 104oF) Temperature Filter Size φ82mm Max. Diameter φ94.4mm / 3.71inch (excluding external tripod mount) **Overall Length** Approx.208.6mm / 8.21inch (from the tip of the lens to the base side of the lens mount)

Weight	Approx. 1570g / 55.38oz (excluding lens cap, lens rear cap, lens hood and external tripod mount) (External tripod mount: Approx. 230g / 8.11oz)
Standard Accessories	Lens cap, Lens rear cap, External tripod mount, Lens hood, Lens storage bag
NOTE	
note	*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

All specifications are subject to change without notice.

© Panasonic