



**LUMIX S 14-28mm F4-5.6 MACRO (S-R1428) L-Mount Lens**  
Wide Angle Zoom Lens

## Lens Construction

---

14 elements in 10 groups (1 aspherical ED lens, 1 aspherical lens, 3 ED lenses, 1 UHR lens)

---

## Mount

---

L-Mount

---

## Focal Length

---

f=14-28mm

---

## Aperture Type

---

7 diaphragm blades / Circular aperture diaphragm

---

## Maximum Aperture

---

F4 (Wide) - F5.6 (Tele)

---

## Minimum Aperture

---

F22

---

## Closest Focusing Distance

---

0.15m / 0.49ft

---

## Maximum Magnification

---

0.5x (at focal length 28mm)

---

## Diagonal Angle of View

---

114°(Wide) - 75°(Tele)

---

## Dust and Splash Resistant

---

Yes\*

\*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

---

## Recommended Operating Temperature

---

-10°C to 40°C (14°F to 104°F)

---

## Filter Size

---

φ77mm

---

## Max. Diameter

---

φ84.0mm / 3.31inch

---

## Overall Length

---

Approx. 89.8mm / 3.54inch (from the tip of the lens to the base side of the lens mount)

---

## Weight

---

Approx. 345g / 0.77lb (excluding lens cap, lens rear cap and lens hood)

---

## Standard Accessories

---

Lens cap, Lens rear cap, Lens hood

---