



LUMIX S PRO 16-35mm F4.0 (S-R1635) L-Mount Lens Wide Angle Zoom Lens

Name

| | |
|----------------------------------|--|
| Lens Construction | 12 elements in 9 groups (3 aspherical lenses, 1 ED lenses, 1 UHR lens) |
| Mount | L-Mount |
| Optical Image Stabilizer | No |
| Focal Length | f=16-35mm |
| Aperture Type | 9 diaphragm blades / Circular aperture diaphragm |
| Maximum Aperture | F4 |
| Minimum Aperture | F22 |
| Closest Focusing Distance | 0.25m / 0.82ft |
| Maximum Magnification | Approx.0.23x |

General

| | |
|--|--|
| Diagonal Angle of View | 107° Wide) - 63° (Tele) |
| Dust and Splash Resistant | Yes* |
| Recommended Operating Temperature | -10oC to 40oC (14oF to 104oF) |
| Filter Size | φ77mm |
| Max. Diameter | φ85mm / 3.34inch |
| Overall Length | 99.6 mm / 3.92inch (from the tip of the lens to the base side of the lens mount) |

Weightapprox.500g /17.63 oz (excluding lens cap, lens rear cap and lens hood)

Standard AccessoriesLens cap, Lens rear cap, Lens hood, Lens storage bag

NOTE

note

*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

All specifications are subject to change without notice.

© Panasonic