



**LUMIX S 20-60mm F3.5-5.6 (S-R2060) L-Mount Lens
Standard Zoom Lens**

Name

Lens Construction	11 elements in 9 groups (2 aspherical lenses, 3 ED lenses, 1 UHR lens)
Mount	L-Mount
Optical Image Stabilizer	No
Focal Length	f=20-60mm
Aperture Type	9 diaphragm blades / Circular aperture diaphragm
Maximum Aperture	F3.5 (Wide) - F5.6 (Tele)
Minimum Aperture	F22
Closest Focusing Distance	0.15m/0.49ft (at focal length 20-26mm) / 0.4m/1.31ft (at focal length 60mm)
Maximum Magnification	0.43x

General

Diagonal Angle of View	94°(Wide) - 40°(Tele)
Dust and Splash Resistant	Yes*
Recommended Operating Temperature	-10°C to 40°C (14°F to 104°F)
Filter Size	φ67mm
Max. Diameter	φ77.4mm / 3.05inch
Overall Length	Approx. 87.2mm / 3.43inch (from the tip of the lens to the base side of the lens mount)

Weight	Approx. 350g / 12.35oz (excluding lens cap, lens rear cap and lens hood)
---------------	--

Standard Accessories	Lens cap, Lens rear cap, Lens hood
-----------------------------	------------------------------------

NOTE

*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

All specifications are subject to change without notice.

© Panasonic