



**LUMIX S 24-105mm F4.0 (S-R24105) L Mount Lens  
Standard Zoom Lens**

## Standard Accessories

---

Lens cap, Lens rear cap, Lens hood, Lens storage bag

---

## NOTE

---

\*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

---

## Features

---

|                                  |   |
|----------------------------------|---|
| <b>Lens Construction</b>         | 16 elements in 13 groups (2 aspherical ED lenses, 2 aspherical lenses, 1 UED lens, 2 ED lenses) |
| <b>Mount</b>                     | L-Mount   |
| <b>Optical Image Stabilizer</b>  | yes   |
| <b>Focal Length</b>              | f=24-105mm  |
| <b>Aperture Type</b>             | 9 diaphragm blades / Circular aperture diaphragm  |
| <b>Maximum Aperture</b>          | F4.0  |
| <b>Minimum Aperture</b>          | F22   |
| <b>Closest Focusing Distance</b> | 0.30m / 0.98ft  |
| <b>Maximum magnification</b>     | Approx. 0.5x  |

---

## General

---

**Diagonal Angle of View** 84°(Wide) - 23°(Tele)

---

|  |  |
|--|--|
| <b>Dust and Splash Resistant</b>         | Yes*   |
| <b>Recommended Operating Temperature</b> | -10oC to 40oC (14oF to 104oF)  |
| <b>Filter Size</b>                       | φ77mm  |
| <b>Max. Diameter</b>                     | φ84mm / 3.31inch   |
| <b>Overall Length</b>                    | Approx. 118mm / 4.65inch (from the tip of the lens to the base side of the lens mount) |
| <b>Weight [g]</b>                        | Approx. 680g (excluding lens cap, lens rear cap and lens hood)                         |
| <b>Weight [oz]</b>                       | Approx. 23.99oz (excluding lens cap, lens rear cap and lens hood)                      |

---

---

All specifications are subject to change without notice.

© Panasonic