



LUMIX S PRO Lens 70-300mm (S-R70300) L-mount Lens  
Telephoto Zoom Lens

## General

<b>Lens Construction</b>	17 elements in 11 groups (2 ED lenses, 1 UED lens, 1 UHR lens)
<b>Mount</b>	L-Mount
<b>Optical Image Stabilizer</b>	Yes
<b>Focal Length</b>	f=70-300mm
<b>Aperture Type</b>	11 diaphragm blades / Circular aperture diaphragm
<b>Maximum Aperture</b>	F4.5 (Wide) - F5.6 (Tele)
<b>Minimum Aperture</b>	F22
<b>Closest Focusing Distance</b>	0.54m/1.77ft (at focal length 70mm) / 0.74m/2.43ft (at focal length 300mm)
<b>Maximum Magnification</b>	0.5x (at focal length 300mm)
<b>Diagonal Angle of View</b>	34°(Wide) - 8.3°(Tele)
<b>Dust and Splash Resistant</b>	Yes*
<b>Recommended Operating Temperature</b>	-10°C to 40°C (14°F to 104°F)
<b>Filter Size</b>	φ77mm
<b>Max. Diameter</b>	φ84.0mm / 3.31inch
<b>Overall Length</b>	Approx.148.0mm / 5.83inch (from the tip of the lens to the base side of the lens mount)
<b>Weight</b>	Approx. 790g / 1.75lb (excluding lens cap, lens rear cap and lens hood)

---

**Standard Accessories**

Lens cap, Lens rear cap, Lens hood

---

**NOTE****NOTE**

\*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

---