

SAFETY DATA SHEET DYNAX S-50 (AEROSOL)

Revision Number 2
Compilation date: 07/07/15
Revision date: 10/03/2023

1.1 Product Identifier

Product name: dynax s-50 (aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Protectant

1.3. Details of the supplier of the safety data sheet

Company name and address:

Bilt Hamber Laboratories Radford Way,
Billericay,
Essex, CM12
0EG United
Kingdom

PPC Co
Unit 1 / 4 Prosperity Parade, Warriewood
NSW 2102 (02) 9999 1222

Tel: 01277 658899

Email: sales@bilthamber.com

1.4. Emergency telephone number

01277 658899 (office hours only)

2. Classification of the substance or mixture

Physical hazards: Aerosol 1 - H222, H229
Health hazards: Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards: Aquatic Chronic 2 - H411

Human health: Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.
Environmental: The product contains a substance which is toxic to aquatic organisms.
Physicochemical: Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Signal word: Danger

Pictogram



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing vapour/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTRE/doctor if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

(Continue...)

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 10/03/2023

Supplementary label information

P264 Wash contaminated skin thoroughly after handling.
P273 Avoid release to the environment.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/ container in accordance with national regulations.

Contains

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, NAPHTHA (PETROLEUM),
HYDROTREATED HEAVY

Supplementary precautionary statements

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous ingredients:

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE CAS number: 68476-85-7 EC number: 270-704-2	10-30%
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280	

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE CAS number: 64742-49-0 EC number: 927-510-4	10-30%
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	REACH registration number: 01-2119475515-33-XXXX

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY CAS number: 64742-48-9 EC number: 919-857-5	10-30%
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	REACH registration number: 01-2119463258-33-XXXX

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.

Ingestion

Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information

See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention or special treatment needed

Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Foam, Carbon dioxide or Dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards: Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for fire-fighters

Protective actions during firefighting: Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions: Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Refer to other sections: For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling requirements:: Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene: Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s): The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³
Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³
Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³
Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³
WEL = Workplace Exposure Limit

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (CAS: 64742-49-0)

DNEL
Consumer - Oral; Long term systemic effects: 149 mg/kg/day
Consumer - Dermal; Long term systemic effects: 149 mg/kg/day
Workers - Dermal; Long term systemic effects: 300 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 447 mg/m³
Workers - Inhalation; Long term systemic effects: 2085 mg/m³

8.2. Exposure controls

Eye/face protection: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection: No specific requirements are anticipated under normal conditions of use.
Other skin and body protection: Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection: No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	
Form:	Aerosol
Colour:	Brown
Odour:	Solvent
Odour threshold:	No information available
pH:	No information available.
Melting point:	No information available.
Initial boiling point and range:	-41 (-41 TO 215)°C @

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

Flash point:	-40°C Closed cup
Evaporation rate:	No information available.
Evaporation factor:	No information available.
Flammability (solid, gas):	No information available.
Lower flammability/explosive limits:	0.6 %
Upper flammable/explosive limit:	9.5 %
Vapour pressure:	No information available.
Vapour density:	No information available.
Relative density:	0.699
Solubility(ies):	Insoluble in water.
Partition coefficient:	No information available.
Auto-ignition temperature:	240°C
Decomposition Temperature:	No information available.
Viscosity:	No information available.
Explosive properties:	No information available.
Oxidising properties:	No information available.

9.2. Other information

Other information: None.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability: The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions: None known.

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid: None known.

10.6. Hazardous decomposition products

Hazardous decomposition products: None at ambient temperatures.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation: May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

Skin contact: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Eye contact: Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards: No known chronic or acute health risks.

Route of exposure: Inhalation Skin and/or eye contact.

Toxicological information on ingredients.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute toxicity - oral
Acute toxicity oral (LD⁵⁰ mg/kg) 5,001.0
Species Rat

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

ATE oral (mg/kg)	5,001.0
Acute toxicity - dermal	
Acute toxicity dermal (LD ₅₀ mg/kg)	2,001.0
Species	Rabbit
ATE dermal (mg/kg)	2,001.0

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Acute toxicity - oral

Acute toxicity oral (LD ₅₀ mg/kg)	5,001.0
Species	Rat
ATE oral (mg/kg)	5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD ₅₀ mg/kg)	3,001.0
Species	Rabbit
ATE dermal (mg/kg)	3,001.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute aquatic toxicity	
Acute toxicity - fish	NOEC, : 1-10 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae
Acute toxicity - microorganisms	LOEC, : 1-10 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Partition coefficient: No information available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

General information:	Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Disposal methods:	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

**SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)**

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE
Proper shipping name (ADN)	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant:



-14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

The Aerosol Dispensers Regulations 2009 (SI2009 No. 2824).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).
Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out

SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET
DYNAX S-50 (AEROSOL)

Revision Number 2
Compilation date: 07/07/15
Revision date: 03/01/18