

Revision Number: 1 Compilation date: 10/03/2023

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE & OF THE COMPANY/UNDERTAKING

1.1 Product identifier Trade name: Dynax-UC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

No further relevant information available

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Bilt-Hamber Ltd Radford Way Billericay Essex CM12 0EG

Further information obtainable from:

Product safety

E-mail: sales@bilthamber.com

Australian Suppler:

Permanent Painted Coatings Unit 1 / 4 Prosperity Parade WARRIEWOOD

N SW 2102 Tel: (02) 9999 0122

1.4 Emergency telephone number: +44 0 1277 658899

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R10-66-67:

Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

2.2 Label elements

Labelling according to EU Guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. The R and S phrases may be omitted if packaging contains no more than 0.125 litres.

(Continue...)



Revision Number: 1 Compilation date: 10/03/2023

Risk phrases:

10 Flammable.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 23 Do not breathe vapour/spray.
- 24 Avoid contact with skin.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

Results of PBT and vPvB assessment

PBT:

Not applicable.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with additions.

Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-<50%
EINECS: 265-150-3	Xn R65	
	R10-66-67	
	Flam. Liq. 3, H226;	
	Asp. Tox. 1, H304;	
	STOT SE 3, H336	

Additional information:

For the wording of the listed risk phrases refer to section 16



Revision Number: 1 Compilation date: 10/03/2023

4. FIRST AID MEASURES

4.1 Description of first aid measures

After skin contact:

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

No special measures required



Revision Number: 1 Compilation date: 10/03/2023

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information

7. HANDLING AND STORAGE

7.1 Precautions for safe handling Use only in well ventilated areas.

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available



Revision Number: 1 Compilation date: 10/03/2023

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Additional information about design of technical facilities:

No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device

Protection of hands:

Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber

Penetration time of glove material

>480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles.



Revision Number: 1 Compilation date: 10/03/2023

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information

Appearance: Form: Liquid Colour: Brown

Odour: Characteristic

Odour threshold: Not determined

pH: Not determined

Melting point: Not determined

Initial Boiling Point/Boiling range: 130°C

Flash point: 40°C

Flammability (solid, gas): Not applicable

Ignition Temperature: 200°C

Decomposition temperature: Not determined

Self-igniting: Product is not self-igniting

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible

Explosive Limits: Upper: 0.6 Vol % Lower: 6.5 Vol %

Vapour pressure at 20°C: 2.1 hPa Vapour density at 20°C: 0.84 g/cm³ Relative density: Not determined Vapour density: Not determined Evaporation rate: Not determined

Solubility in/ miscibility with water: Not miscible or difficult to mix

Partition coefficient: Not determined

Viscosity:

Dynamic: Not determined Kinematic At 20 °C: 20 s

Solvent content:

Organic solvents: 44.6% **Solids content:** 55.4 %

9.2 Other information: No further information available.

VOC (EU): 44.60 % VOC (EU): 374.6 g/l VOCV: 44.6%



Revision Number: 1 Compilation date: 10/03/2023

10. STABILITY AND REACTIVITY

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:		
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

Primary irritant effect:

On the skin:

No irritant effect.

On the eye:

No irritating effect.

Sensitisation:

No sensitising effects known



Revision Number: 1 Compilation date: 10/03/2023

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available



Revision Number: 1 Compilation date: 10/03/2023

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION,
	SUPPLY AND USE (MFSU) OF
	COATINGS (PAINTS, VARNISHES AND VI
	TREOUS ENAMELS), ADHESIVES, SEALANTS
	AND PRINTING INKS
08 01 00	Wastes from MFSU and removal of paint and varnish
08 01 11*	Waste paint and varnish containing organic solvents or
	other dangerous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations

14. TRANSPORT INFORMATION

4441111111	
14.1 UN-Number	UN1139
ADR, IMDG, IATA	
14.2 UN proper shipping name	1139 COATING SOLUTION, special provision 640E
ADR	
IMDG, IATA	COATING SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
14.4 Packing group	III
ADR, IMDG, IATA	
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E,S-E
14.7 Transport in bulk according to Annex II of	Not applicable.
MARPOL73/78 and the IBC Code	
Transport/Additional information:	For ADR and IMDG: Transport and packing are in
	accordance with the regulation for limited quantities.
	These products are therefore classified as no dangerous
	goods.
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E

(Continue...)



Revision Number: 1 Compilation date: 10/03/2023

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litres.

Risk phrases:

10 Flammable.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 23 Do not breathe vapour/spray.
- 24 Avoid contact with skin.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste

National regulations -

Technical instructions (air):

Class	Share in %
NK	44.6

Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Other regulations, limitations and prohibitive regulations

Please note:

2-1

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out



Revision Number: 1 Compilation date: 10/03/2023

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS:

Research & Development

Contact:

sales@bilthamber.com

(+44)1277 658899