

PPC MARINE CLEAN - Degreaser

Application Information

PRODUCT DESCRIPTION:

MARINE-CLEAN cleans and degreases in one application without leaving residues, noxious fumes or flammable solvents.

MARINE CLEAN is a complex mixture of organic and inorganic chemicals. It is non-toxic, biodegradable, water -based, and has no noxious odours nor chlorinated solvents. It doesn't contain any petroleum products and has no flash point. Marine-Clean represents a revolutionary breakthrough in cleaners, de-greasers and dispersants.

MARINE CLEAN USES:

Pre-paint cleaning and degreasing prior to the application of paint or primer to aid coating adhesion.

Removal of dirt, grease, and soil from components to avoid contamination.

Cosmetic cleaning of components or surfaces after use, disassembly ...

Pre-plate cleaning prior to plating, welding, anodizing, or similar surface finishing to aid adhesion.

Pre-bond cleaning prior to the application of an adhesive or sealant to aid in bonding one surface or component to another.

For cleaning and degreasing:-

5	0	0
Machinery parts		Turbine blades
Diesel engines		Compressors
Transformers		Bulkheads
Deck plates		Bilge areas
Removal of oily deposits found in closed systems such		

as'-

Air conditionina **Boiler tubes** Compressor lines Heat exchanges and coils Removal of :-

Light distillates, mineral oils, heavy grease.

De Greasing:-

All metal surfaces Plastics Wood Fibreglass

Painted surfaces.

Remember to thoroughly rinse off Marine Clean with water after Completing your cleaning job.

APPLICATION:

- For general usage dilute with 50% Hot Water, spray or brush and leave for 30 minutes.
- Wash off well prior to applying Metal Ready or painting.
- If in doubt as to Marine Clean reaction to existing paint, fibreglass etc., dilute with 80 parts water and 20 parts Marine Clean. Increase this dilution gradually. (more Marine Clean)

FEATURES:

- Biodegradable aqueous cleaning agent.
- Low suds.
- Broad materials and surface compatibility.
- Non-corrosive.
- Does not contain petroleum or caustic chemicals.
- Non-flammable.

FREQUENTLY ASKED QUESTIONS:

Should Marine Clean be diluted with water?

Yes. Marine Clean will actually be more effective if it is diluted at least 1:1 with water.

Does Temperature affect the cleaning action?

Yes. A hot solution will work better and faster, so dilute with hot water and store Marine Clean indoors.

What dilution is most effective?

That depends on the job to be done. 1:1 is best for engine cleaning, removed baked-on oil from cylinder heads, removing gum and varnish from fuel tanks. To clean exterior surfaces of cars or boats, use dilutions beginning at 1 part Marine Clean to 5 parts water through to 10 parts water. Always remember to thoroughly rinse off Marine Clean with water after completing your cleaning job.

How fast will Marine Clean do the job?

That also depends on the job. Baked-on oil may take up to 2 hours of soaking before it can be easily brushed or sponged off; gum and varnish in a fuel tank may take 24 hours or more. Hot solution works better.

Does metal that has been cleaned with Marine Clean have to be treated with Metal Ready before sealing tank with Fuel Tank Sealer? Yes. Marine Clean is a powerful caustic solution that leaves an Alkaline finish on metal. An acid finish takes paint better because it etches the metal and gives it a surface profile with "tooth" for the Topcoat paint to bite into. Our Metal-Ready Rust Remover/ Preprimer is the perfect prep to use on any surface that's been cleaned with Marine Clean first.

Cleaning the walls of your house": Mix one litre in a bucket of water, thorough wet the walls of the house with a hosepipe, apply the Marine Clean mixture with a bristle broom, then rinse the walls well with the hosepipe, watch the grease and grim wash away.

ALWAYS WEAR EYE PROTECTION AND RUBBER GLOVES WHEN USING MARINE CLEAN.

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or

The information set out in this filer is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use of the Products sold by Permanent Painted Coatings Pty Ltd (Australia)("PPC Pty Ltd") are beyond the control of PPC Ltd / and or PPC Pty Ltd ('the company), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein. The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breachof the aforesaid warranty shallbe limited, at the option of the Company, to payment of the cost of replacing the Products or of acquining equivalent products and in no case shall the Company be liable for consequential loss or defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unvirten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

PERMANENT PAINTED COATINGS LTD

Unit 1 / 4 Prosperity Parade; WARRIEWOOD NSW 2102 Phone free: 1-800 643 229 Telephone: 02 9999 0122 Fax: 02 9999 0394 Wwebsite: www.ppcco.com.au Email: sales@ppcco.com.au

