

## Rust Encapsulator Matte Black Finish

### SECTION 1 - IDENTIFICATION

**Product Identifier**

**Product Number(s)** 16065ZP, 16063ZP, 16070ZP  
**Product Name** Rust Encapsulator Matte Finish Black - 16065ZP - Quart  
 Rust Encapsulator Matte Finish Black - 16063Z - Pint - INACTIVE  
 Rust Encapsulator Matte Finish Black - 16070ZP - Gallon

**24 hr Emergency  
Phone Number**

**800-424-9300**  
(Chem-Trec)

**Other Means of Identification** None

**Recommended Use and Restrictions on Use**

**Recommended Use** Rust preventative  
**Restrictions on Use** None Identified

	SUPPLIER DETAILS
Australian Supplier: Permanent Painted Coatings Unit 1 / 4 Prosperity Parade WARRIEWOOD NSW 2102 Tel: (02) 9999 0122	<b>Name</b> The Eastwood Company <b>Address</b> 263 Shoemaker Road Pottstown PA 19464 <b>Phone Number</b> 610-323-2200 <b>Fax Number</b> 610-323-6268

### SECTION 2 - HAZARD(S) IDENTIFICATION




**Hazard Classification**

HEALTH HAZARDS				PHYSICAL HAZARDS			
Acute Tox. Oral	<input type="checkbox"/>	Mutagenicity	<input type="checkbox"/>	Unstable Explosive	<input type="checkbox"/>	Refrigerated Liq. Gas	<input type="checkbox"/>
Acute Tox. Skin	<input type="checkbox"/>	Carcinogenicity	2	Explosive	<input type="checkbox"/>	Flammable Liquid	2
Acute Tox. Inhalation	<input type="checkbox"/>	Tox. to Reproduction	2	Flammable Gas	<input type="checkbox"/>	Flammable Solid	<input type="checkbox"/>
Skin Irritation	<input type="checkbox"/>	STOT SE	<input type="checkbox"/>	Aerosol	<input type="checkbox"/>	Self-Reactive Sub.	<input type="checkbox"/>
Eye Irritation	2	STOT RE	2	Oxidizing Gas	<input type="checkbox"/>	Pyrophoric Liquid	<input type="checkbox"/>
Resp. Sensitization	<input type="checkbox"/>	Aspiration Hazard	1	Gas Under Pressure	<input type="checkbox"/>	Self-Heating Substance	<input type="checkbox"/>
Skin Sensitization	<input type="checkbox"/>			<b>ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)</b>			
	<input type="checkbox"/>		<input type="checkbox"/>	Aquatic Acute	<input type="checkbox"/>	Aquatic Chronic	<input type="checkbox"/>
	<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	Ozone Depleting	<input type="checkbox"/>

**Signal Word**

Danger!

**Hazard Pictograms**
**Hazard Statements**




 Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Precautionary Statements**

**General** Keep out of reach of children.

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2022

Revision 6

Page 2 of 8

<b>Prevention</b>	<i>Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe fumes. Wash hands thoroughly after handling. Wear protective gloves and eye protection.</i>
<b>Response</b>	<i>If exposed, concerned or feel unwell: Call a doctor. IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. In case of fire: Use water, CO2, dry chemical or universal aqueous film forming foam to extinguish.</i>
<b>Storage</b>	<i>Store in a well-ventilated place. Store locked up. Keep cool.</i>
<b>Disposal</b>	<i>Dispose of contents/container in accordance with local regulations.</i>
<b>Hazards Not Otherwise Classified</b>	<i>None identified.</i>
<b>Unknown Acute Toxicity</b>	<i>36 % by wt</i>

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	% WT RANGE*
1	Tert-Butyl Acetate	0000540-88-5	15 - 40
2	V M & P Naphtha	0064742-89-8	7 - 13
3	Acetone	0000067-64-1	7 - 13
4	Methyl Acetate	0000079-20-9	5 - 10
5	Carbon Black	0001333-86-4	1 - 5
6	Stoddard Solvent	0008052-41-3	1 - 5
7	Toluene	0000108-88-3	1 - 5
8	Xylene	0001330-20-7	0.5 - 1.5

\* Exact percentages of composition withheld as trade secret

## SECTION 4 - FIRST AID MEASURES

### Description of First-Aid Measures

<b>General</b>	<i>If exposed or concerned seek medical advice/attention.</i>
<b>Eye Contact</b>	<i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i>
<b>Skin Contact</b>	<i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i>
<b>Ingestion</b>	<i>Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i>
<b>Inhalation</b>	<i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i>
<b>First-Aid Responder Protection</b>	<i>Wear adequate personal protective equipment based on the nature and severity of the emergency.</i>

### Most Important Symptoms and Effects, Both Acute and Delayed

<b>Eye Contact</b>	<i>Liquid contact may cause pain along with moderate eye irritation.</i>
<b>Skin Contact</b>	<i>Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.</i>
<b>Ingestion</b>	<i>May cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary oedema.</i>
<b>Inhalation</b>	<i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i>

### Indication of Immediate Medical Attention and Special Treatment

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2022

Revision 6

Page 3 of 8

<b>Notes to Physician</b>	<i>Stoddard Solvent sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed. Use of sympathomimetic drugs should be avoided. If ingested, the material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left later lateral decubitus position.</i>
<b>Specific Treatments/Antidotes</b>	No information available.
<b>Immediate Medical Attention</b>	No information available.

## SECTION 5 - FIRE-FIGHTING MEASURES

### Extinguishing Media

<b>Suitable Extinguishing Media</b>	Water, CO <sub>2</sub> , dry chemical, or universal aqueous film forming foam
<b>Unsuitable Extinguishing Media</b>	Water jet

### Specific Hazards Arising from the Chemical or Mixture

<b>Decomposition Products</b>	Oxides of carbon (CO, CO <sub>2</sub> ), smoke, and/or vapors
<b>Hazards from the Product</b>	CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

### Advice for Firefighters

<b>Protective Actions</b>	Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.
<b>Protective Equipment</b>	As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

<b>For Non-Emergency Personnel</b>	No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
<b>For Emergency Responders</b>	Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.

### Environmental Precautions

<b>Precautions</b>	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
--------------------	---

### Methods and Materials for Containment and Cleaning Up

<b>Containment Procedures</b>	Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
<b>Cleanup Procedures</b>	Avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
<b>Other Information</b>	The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
<b>Prohibited Materials</b>	Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

## SECTION 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

<b>General Handling Precautions</b>	KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Applications using Flammable and Combustible Materials is recommended.
<b>Hygiene Recommendations</b>	Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

### Conditions for Safe Storage Including Any Incompatibilities

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2022

Revision 6

Page 4 of 8

## Storage Requirements

Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.

Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

## Incompatibilities

Segregate storage away from materials indicated in Section 10

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control Parameters

#### Occupational Exposure Limits

ID	PEL	OSHA STEL	CEILING	IDLH	RFL	NI SH	STEL	CEILING	TLV	ACGIH STEL	CEILING	AIHA WFEEL
1	200 ppm	-	-	1500 ppm	200 ppm	-	-	1800 mg/m3	200 ppm	-	-	-
3	1000 ppm	-	-	2500 ppm	250 ppm	-	-	-	250 ppm	500 ppm	-	-
4	200 ppm	-	-	3100 ppm	200 ppm	250 ppm	-	-	200 ppm	250 ppm	-	-
5	3.5 mg/m3	-	-	1750 mg/m3	3.5 mg/m3	-	-	-	3 mg/m3	-	-	-
6	500 ppm	-	-	20000 mg/m3	350 mg/m3	-	-	1800 mg/m3	100 ppm	-	-	-
7	200 ppm	-	300 ppm	500 ppm	100 ppm	150 ppm	-	-	50 ppm	150 ppm	-	-
8	100 ppm	-	-	900 ppm	100 ppm	150 ppm	-	-	100 ppm	150 ppm	-	-

#### Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
3	Acetone in urine	End of shift	50 mg/L	Ns
7	o-Cresol in urine	End of shift	0.5 mg/L	B
8	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine	-

#### Other Control Parameters

Not Available

### Appropriate Engineering Control

#### Engineering Measures

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

### Individual Protection Measures

#### Hygiene Considerations

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

#### Thermal Protection

This product does not present a thermal hazard.

#### Respiratory Protection

An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

#### Skin Protection

For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

#### Eye/Face Protection

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

#### Other Protective Equipment

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### Physical Properties

#### Boiling Point

> 55.0 °C (131.0 °F)

#### Melting / Freezing Point

Not Determined

#### Flash Point, Liquid

> -20.0 °C (-4.0 °F)

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2016

Revision 6

Page 5 of 8

<b>Explosive Limits</b>	0.70% - 16.00%	<b>Autoignition Temperature, Liquid</b>	Not Determined
<b>Flammability</b>	Category 2 Liquid	<b>Relative Density (H2O = 1)</b>	0.944 g/cc
<b>Molecular Weight</b>	Not Available	<b>Weight</b>	7.875 lbs/gal
<b>Vapor Pressure</b>	Not Determined	<b>pH</b>	Not Available
<b>Vapor Density</b>	6.240 g/cc Maximum	<b>Evaporation Rate</b>	Not Available
<b>Form</b>	Liquid	<b>Partition Coefficient</b>	Not Available
<b>Viscosity</b>	Not Available	<b>Refractive Index</b>	Not Available
<b>Odor Threshold</b>	Not Available	<b>Heat of Combustion (t-Hc)</b>	Not Available
<b>Odor</b>	Paint-like	<b>Water Solubility</b>	Not Available
<b>Appearance / Color</b>	Black coating	<b>Decomposition Temperature</b>	Not Available

**Air Quality Properties**

<b>Percent Volatile</b>	61% Wt (69% Vol) Max	<b>VOC Regulatory</b>	4.286 lbs/gal (513.532 g/L)
<b>Percent VOC</b>	45% Wt (52% Vol) Max	<b>VOC Actual</b>	3.534 lbs/gal (423.403 g/L)
<b>Percent HAP</b>	4% Wt (4% Vol) Max	<b>HAP Content</b>	0.246 lbs/gal (29.419 g/L)
<b>Solids/Non Volatile Content</b>	40% Wt (32% Vol) Max	<b>Maximum Incremental Reactivity</b>	0.472 g O3/g
<b>Global Warming Potential</b>	0.103		

## SECTION 10 - STABILITY AND REACTIVITY

<b><u>Reactivity</u></b>	No specific test data related to reactivity is available for this product or its ingredients.
<b><u>Chemical Stability</u></b>	This product is stable.
<b><u>Hazardous Reactions</u></b>	Under normal conditions of storage and use, hazardous reactions are not expected to occur.
<b><u>Conditions to Avoid</u></b>	Keep away from heat, sparks, flame, and red hot metal.
<b><u>Material Incompatibility</u></b>	Acids, Activated Carbon, Alkalis, Dichlorohydrantion, Hexachloromelamine, Hydrogen Peroxide, Isoprene, Nitrates, Nitric Acid, Nitrogen Tetroxide, Potassium Tert-Butoxide, Silver Perchlorate, Strong Acids, Strong Oxidizing Agents, Strong Reducing Agents, Sulfur Dichloride, Tetranitromethane, Trichloromelamine, Uranium Hexafluoride
<b><u>Decomposition Productions</u></b>	Oxides of Carbon, Acetic Acid, Formaldehyde fumes, Hydrogen Peroxide, Methanol, tert-Butanol may be formed depending on fire conditions.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Acute Toxicity Estimates (mixture)**

<b>Oral LD<sub>50</sub></b>	3961 mg/kg
<b>Dermal LD<sub>50</sub></b>	4567 mg/kg
<b>Inhalation LC<sub>50</sub></b>	4621 mg/L 4-hour

**Acute Toxicity on Ingredients**

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	4100 mg/kg	rat	-	-	-	-	-
2	5000 mg/kg	rat	3000 mg/kg	rat	3400 ppm	4h	rat
3	5800 mg/kg	rat	20000 mg/kg	rabbit	50100 mg/m3	8h	rat
4	>5000 mg/kg	rat	>5000 mg/kg	rat	>16000 ppm	4h	rat
5	>15400 mg/kg	rat	>3000 mg/kg	rabbit	6750 mg/m3	4h	rat
6	>5000 mg/kg	rat	>3000 mg/kg	rabbit	>5500 mg/L	4h	rat
7	636 mg/kg	rat	>12000 mg/kg	rabbit	49000 mg/m3	4h	rat
8	4300 mg/kg	rat	4500 mg/kg	rabbit	6700 mg/L	4h	rat

**Health Hazard Classification**

<b>Skin Corrosion / Irritation</b>	Classification criteria not met
<b>Eye Damage / Irritation</b>	Category 2
<b>Respiratory Irritation</b>	Classification criteria not met

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2016

Revision 6

Page 6 of 8

## Rust Encapsulator Matte Black Finish

<b>Respiratory / Skin Sensitization</b>	Category 1
<b>Germ Cell Mutagenicity</b>	Classification criteria not met
<b>Reproductive Toxicity</b>	Category 2
<b>STOT - Single Exposure</b>	Classification criteria not met
<b>STOT - Repeated Exposure</b>	Category 2
<b>Aspiration Hazard</b>	Category 1
<b>Carcinogen Data</b>	

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
5	Yes	-	App A & C	A3	-	2B

### Information on the Likely Routes of Exposure

**Routes of Exposure** Skin contact, skin absorption, eye contact, inhalation, ingestion

### Information on Physical, Chemical and Toxicological Effects

**Symptoms of Exposure** Abdominal Cramps, Central Nervous System Depression, Chemical Pneumonitis, Chest Tightness, Cough, Dermatitis, Dizziness, Drowsiness, Excitation, Optic Nerve Atrophy, Skin Irritation, Staggering Gait, Throat Irritation, Upper Respiratory System Irritation, Vomiting

### Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

**Delayed Effects** No known delayed effects.

**Immediate Effects** No known immediate effects.

**Chronic Effects** Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal. Stoddard Solvent when ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Reports of chronic poisoning from Toluene describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect a developing fetus.

**Medical Conditions Aggravated** May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

**Target Organs** Bladder, Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Kidneys, Liver, Respiratory System, Skin

## SECTION 12 - ECOLOGICAL INFORMATION

### Acute Aquatic Toxicity

ID	TYPE	FISH VALUE	PERIOD	TYPE	INVERTEBRATES VALUE	PERIOD	TYPE	AQUATIC PLANTS VALUE	PERIOD	TYPE	MICROORGANISMS VALUE	PERIOD
1	LC50	361 mg/L	96h	EC50	3968 mg/L	48h						
3	LC50	13.5 mg/L	96h	EC50	8800 mg/L	48h	NOEC	530 mg/L	8d	EC5	1700 mg/L	16h
4	LC50	180 mg/L	96h	EC50	1027 mg/L	48h	EC50	>120 mg/L	72h	EC50	6100 mg/L	30m
5	NOEC	1000 mg/L	96h	EC50	>5600 mg/l	24h	-	-	-	EC0	400 mg/L	3h
7	LC50	5.8 mg/L	96h	EC50	6 mg/L	48h	IC50	12 mg/L	72h	EC50	20 mg/L	30m
8	LC50	26.7 mg/L	96h	EC50	14 mg/L	24h	-	-	-	-	-	-

### Ecological Data

ID	PERSISTENCE	PERSISTENCE AND DEGRADABILITY BOD	COD	ThOD	BIOACCUMULATIVE POTENTIAL Pow / Kow	BCF	MOBILITY Koc
2	95% / 28 days	-	-	-	2.1 log Kow	-	-
3	90.9% / 28 days	1.85 mg/g / 5d	2.07 mg/g	2.21 mg/g	-0.24 log Pow	0.69 BCF	1.26 log Koc
4	-	-	1511.8 mg/g	1510 mg/g	0.18 log Pow	-	0.68 log Koc
5	-	5 mg/L	-	-	1.09 log Pow	0.599 log BCF	1.99 log Koc
6	-	-	-	-	3.16 log Kow	-	-
7	86% / 20 days	2.15 mg/g	2.52 mg/g	3.13 mg/g	2.65 Pow	1.57 log BCF	2.15 log Koc
8	-	0.64 mg/L	-	2410 mg/g	3.271 log Pow	2.2557 log BCF	3.156 log Koc

**Other Adverse Effects** No additional information available.

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2016

Revision 6

Page 7 of 8

## SECTION 13 - DISPOSAL CONSIDERATIONS

**Waste Disposal**

Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

**Waste Disposal of Packaging**

Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallon or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.

**Landfill Precautions**

Not Available

**Incineration Precautions**

Not Available

## SECTION 14 - TRANSPORTATION INFORMATION

**Transportation Information**

**Ground Transportation (DOT)**

**Air Transportation (IATA)**

**Ocean Transportation (IMDG)**

UN Number

UN1263

UN1263

UN1263

Proper Shipping Name

Paint Related Material, Limited Quantity    Paint Related Material, Limited Quantity    Paint Related Material, Limited Quantity

Hazard Class(es)

3

3

3

Packaging Group

II

II

II

Marine Pollutant

No

No

No

Hazard Label(s)



## SECTION 15 - REGULATORY INFORMATION

**Federal Regulations**

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN WATER ACT SOCMI	CLEAN WATER ACT
1	Yes	-	-	5000	-	Yes	-	-	-	-	-	-	-
2	Yes	-	-	-	-	-	-	Yes	-	-	-	-	-
3	Yes	-	U002	5000	-	Yes	-	Yes	-	-	-	-	-
4	Yes	-	-	-	-	Yes	-	Yes	-	-	-	-	-
5	Yes	-	-	-	-	-	-	-	-	-	-	-	-
6	Yes	-	-	-	-	-	-	Yes	-	-	-	-	-
7	Yes	-	U220	1000	2%	Yes	-	Yes	Yes	-	Yes	Yes	1000 (PP)
8	Yes	-	U239	100	1%	Yes	-	Yes	-	-	Yes	Yes	100

**State Regulations**

ID	CA P-65	DE RQ	MA RTK CODES	TYPE	E RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1	-	5000	2,4 F8	-	-	AO	-	-	-	5000	1	-	Yes-E	200 ppm	-	-
3	-	5000	2,4,5,6 F8 F9	-	20000	AON	-	-	-	5000	1	-	Yes-E	750 ppm	-	-
4	-	-	2,4,5,6	-	-	AO	-	-	-	-	-	-	Yes	200 ppm	-	-
5	C	-	2,4 F5	-	-	ANOR	-	-	-	-	-	-	Yes	3.5 mg/m3	A	-
6	-	-	2,4	-	-	-ANO	-	-	-	-	-	-	Yes	100 ppm	A	-
7	D	1000	2,4,5,6 F7 F8 F9	-	2000	ANO	1	1	-	1000	1	-	Yes-E	100 ppm	A	-
8	-	100	2,4 F8 F9	-	2000	ANO	1	-	-	1000	1	-	Yes-E	100 ppm	A	-

# SAFETY DATA SHEET

Part No. See Below Liquid

February 23, 2016

Revision 6

Page 8 of 8

## SECTION 16 - OTHER INFORMATION

### SDS Revision History

Revision 4, 01/30/2006, General update.  
Revision 5, 05/01/2012, Packing Group change.  
Revision 6, 02/23/2016, Updated to GHS Version 3 Format.

### SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department.

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.