



Application Information

TOUCH-LESS is our new eco-friendly pressure-washer, pre-clean, snow foam which can be applied by pump spray or trigger too.

Applied at typically a 4% PIR this bio-degradable sugar-based product provides truly exceptional levels of cleaning of automotive paintwork.

Unlike other petrochemical-based cleaners TOUCH-LESS is free-and-easy rinsing, easing the effort of subsequent bucket washes and massively helping post-treatments bond too.

TOUCH-LESS also contains corrosion inhibitors. Packed in 5 litre pH ~12, contains no phosphates, solvents, NTA, or caustic soda.

TOUCH-LESS is designed to allow for superior and simple application of our new paint protection product TOUCH-ON.

HOW TO USE

TOUCH-LESS may be applied with trigger spray, pump spray, pressure washer, or snow foam lance. The minimum recommended dilution rate should be 2% PIR (Panel Impact Ratio) and up to 5% for very dirty vehicles. Where application is through trigger spray or pump spray, the dilution calculation is easy to achieve, however, for application with pressure equipment it is essential to determine the amount of water being delivered to the equipment reservoir.

Step 1 - Fill the detergent bottle or reservoir (on machine or lance) up to capacity with plain water. Turn detergent feed to full. Take a large bucket or container and discharge the lance into this, watching the detergent bottle until empty. Once empty, stop.

Step 2—The following calculations will achieve 4% dilution; Measure the total amount collected and multiply this number by 0.04 (Total can be measured in either volume with a measuring jug or by weight) this is the amount of TOUCH-LESS to use.

Step 3 -Add the calculated amount from STEP TWO to the pressure-washer reservoir and top up to full with cold water and shake in for a few moments.

Step 4—Apply touchless to entire vehicle or panel by panel. Allow to soak for 1-5 minutes (but never allow to dry). Power-wash off.

It is not necessary to use all diluted touch-less in one wash. One litre of diluted product should last 4-5 washes. Apply to cool panels in shaded conditions. Do not allow this product to dry in use. Keep the bottle neck and lid clean.

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee.

Since the conditions of use of the Products sold by Permanent Painted Coatings Limited Permanent Painted Coatings Pty Ltd (Australia) ("PPC Pty Ltd") are beyond the control of PPC Ltd / and or PPC Pty Ltd ("the company"), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein.

The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breach of the aforesaid warranty shall be limited, at the option of the Company, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Companies be liable for consequential loss or damage.

In no case will the Company be liable to defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

Imported and distributed by:

PERMANENT PAINTED COATINGS PTY LTD
1/4 Prosperity Parade, Warriewood, NSW 2102.

For your nearest retail outlet

PHONE FREE 1-800 643 229; PHONE: 02 9999 0122;

Website: www.ppcco.com.au

Email:

