

# PRIMAX<sup>TM</sup> MAGIC BOND

## GENERAL DESCRIPTION

Primax Magic Bond is a single component cementations thick/thin bed material made with finest aggregates and the best quality additives. Specially formulated to bond a variety of tiles onto wall and floor. Only requires addition of water

**PACK SIZE**                      20 kg, 40 kg

**COLOUR RANGE**              Grey only

## RECOMMENDED USES

- New tiling in internal & external areas.
- For walls & Floor tiling.
- Suitable for heavy commercial and industrial applications.
- Tiling corridors, pavements, podiums and roofs.

## STORAGE

Sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +35°C. Protect from direct sunlight. Protect from humidity.

## LIMITATIONS

Don't exceed the tile bond/water ratio  
Keep the product away from moisture and dampness

## MIXING

- The mixing ratio of Magic Bond is 20kg of powder to 5 liters of water.
- Pour 5 liters of clean water into a drum and then gradually add the Magic Bond while mixing continuously until a smooth lump free mix is obtained.
- Allow the mix to stand for 5 minutes, re-stir and then apply the adhesive onto the substrate.

## SUBSTRATE PREPARATION

The substrate must be solid, clean and load-bearing. Oil stains, bond-inhibiting surfaces and contaminations must be thoroughly removed. Irregularities on walls or floors are to be leveled.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

- Hazardous - contains cement silica.
- Wear gloves and mask when handling.
- Wash hands thoroughly after use.
- Manual handling of this bag without due care and attention may result in personal injury



**PRIMAX**<sup>TM</sup>  
**PAINTS**