

# HI-BUILD<sup>®</sup> ROAD LINER ENAMEL

Primax Road Liner Enamel is fast-drying color stable high build alkyd traffic road marking paint that has excellent adhesion to only cured asphalt, concrete, brick, and other surfaced highways.

**PACK SIZE:** 3.64 L

**COLOR RANGE:**

White, Yellow & Black

**COMPOSITION (NOMINAL):**

Pigment: Light Fast Pigments

Binder: Modified Alkyd

Solvent: Xylene

**FLASHPOINT:**

34°C

**DRYING TIME:**

Depends on temperature, humidity, air movements, and film thickness

Touch Dry 1 - 2 Hours

Recoat 3- 4 Hours

**APPLICATION:** Spray, Roller & Brush

**CLEANING UP:**

Clean all equipment with Primax N.C. thinner immediately after use.

**THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 10 – 12 m<sup>2</sup> /liter /coat.

**SURFACE PREPARATION:**

The surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, and other foreign material to ensure adequate adhesion.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION**

Material health and safety data sheet are available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during the application and drying of the paint. Avoid inhalation of paint mist and vapors and skin contact. Spillage of paint on the skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



**PRIMAX**<sup>TM</sup>  
**PAINTS**