

HI-BUILD[®] ROAD MARKING PAINT

Primax Road Marking Paint made according to modern Western technologies with the use of imported raw material, represents a suspension of a white pigment and fillers in polycondense binding. The paint forms an even, homogeneous, matte film without extraneous inclusions.

PACK SIZE: 3.64 L

COLOR RANGE: White/Red/Yellow & Black

COMPOSITION (NOMINAL):

Pigment: Light Fast Pigments

Binder: Modified Alkyd

Solvent: Xylene

FLASH POINT: 34°C

DRYING TIME:

Depends on temperature, humidity, air movements, and film thickness

Touch Dry 1 – 2 hours

Recoat 3– 4 Hours

APPLICATION:

Spray, Roller & Brush

CLEANING UP:

Clean all equipment with Primax N.C thinner immediately after use.

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 10 – 12 m² /liter /coat.

SURFACE PREPARATION:

The surface can be cleaned by wire brushing or Air pressure, surface should be dry and free from dirt, paint rust oil, grease, etc. Road marking is recommended for marking, ground marker, Machinery wall, and C.C wall Marker.



PRIMAXTM
PAINTS

SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep the container tightly closed, upright, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter, etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink, and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, masks, and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to the eyes, skin, and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse your mouth with plenty of water (only if the person is unconscious) and show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated places. Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



PRIMAXTM
PAINTS