

PRIMAX™ WOOD CARE N.C GLOSS LACQUER

PRODUCT DESCRIPTION:

Primax Wood Care N.C Clear Gloss Lacquer is a fast drying nitrocellulose based topcoat with a Highly Glossy & Matt look. Gives a durable rich finish. Easy to apply on various surfaces for decorative purposes with protection. The finish is weather resistant.

PACK SIZE: 0.91 L 3.64 L

COLOR RANGE: Clear

COMPOSITION (NOMINAL):

Pigment: N/A

Binder: Nitrocellulose, Alkyd

Solvent: Volatile solvents BA, IPA, XYLENE

FLASH POINT: Matt: 16°C / Gloss: 15.5°C

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 15 - 20 Minutes

Recoat: 1- 1 1/2 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 11-13 m² /litre /coat.

APPLICATION: Spray

THINNING:

Conventional spray: 50 - 60% with Primax Wood Care Thinner.



PRIMAXTM
PAINTS

CLEANING UP:

Clean all equipment with Primax Wood Care Thinner immediately after use.

SURFACE PREPARATION:

Before application, the surface should be clean dry, and free from oil, grease, dust, wax etc. Rub down the surfaces with the help of abrasive paper. Clean with the help of clean cloth. Apply 1-2 coats of Primax Wood Care N.C. Sanding Sealer. Allow it to dry. Slightly rub down the surfaces with the help of abrasive paper after each coat. Clean with the help of clean cloth. Apply 2-3 coats of Primax Wood Care Lacquer Matt &Gloss. Stir the product thoroughly before use.

SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION:

Highly inflammable. Keep the container tightly closed, up right, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of paint waste in accordance with the appropriate environment quality regulation.

