

PRIMAX™ N.C THINNER

PRODUCT DESCRIPTION:

Primax Nitro Cellulose Thinner is Super grade NC THINNER based on a mixture of esters, glycol, aromatic solvents and ketones, provide a suitable diluents to all nitro products.

PACK SIZE: 3.64 L

COLOR RANGE: Clear

COMPOSITION (NOMINAL):

Pigment: N/A

Binder: N/A

Solvent: Volatile solvents BA, IPA, XYLENE

FLASHPOINT: 29°C

DRYING TIME:

Depends on temperature, humidity, air movements, and film thickness

Touch Dry: N/A

Recoat: N/A

APPLICATION: Spray

CLEANING UP:

Clean all equipment with Primax N.C Thinner immediately after using NC Products.

THEORETICAL COVERAGE: N/A



SURFACE PREPARATION:

This Thinner can be used in Primax Wood Care N.C Products.

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



PRIMAXTM
PAINTS