

POWER[®] ECONOMY SYNTHETIC UNDERCOAT

Primax Power Economy Synthetic Undercoat is quick drying undercoat with excellent filling and good adhesion properties. Overnight air drying makes the primer easily sand able. It can be over coated with synthetic enamel, hammer tone and metallic finishes including automotive lacquers.

PACK SIZE: 0.91 Litre, 3.64 Litre.

COLOR RANGE: White Only

COMPOSITION (NOMINAL):

Pigment: Lightfast Pigments & Inert Fillers

Binder: Alkyd Resin

Solvent: Mineral turpentine

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 1-2 Hours

Recoat: 4-6 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 9-11m²/litre/coat.

APPLICATION:

Brush Roller Spray

THINNING:

Mineral Turpentine / Primax Mixing Oil

Brush or Roller: 10-25%

Conventional spray: 30-40%

FLASH POINT:

34 degree C



PRIMAXTM
PAINTS

RECOMMENDATIONS:

Conventional spray is satisfactory through most equipment.

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATIONS:

Prior to starting painting surface should be clean, and free from dirt, grease, and other foreign materials for achieving good results. Apply two coats of Primax Synthetic Undercoat. Give 8-16 hours between the coats for drying. As the undercoat is highly pigmented it should not be left unpainted for a long time. After overnight hard drying the surface is sanded / wet flatted with 320 or 400-grade sanding paper. Wipe the surface dry and then with a petrol-soaked cloth to get rid of oily finger marks before over-coating.

SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION:

Highly inflammable. Keep the container tightly closed, upright, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink, and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, masks, and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to the eyes, skin, and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse your mouth with plenty of water (only if the person is unconscious) and show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.



PRIMAXTM
PAINTS