

POWER[®] WALL PUTTY

GENERAL DESCRIPTION Primax Power Wall Putty is a high quality ready to use filler for all types of interior masonry surface such as brick work, plaster and cement rendering.

PACK SIZE 20 kg Only

COLOUR RANGE White Only

COMPOSITION (NOMINAL) Pigment: Inert Fillers
Binder: PVA Copolymer Emulsion.
Solvent: Water

DRYING TIMES Depends on temperature, humidity, air movements, and film thickness.

Touch dry 2 - 3 Hours

Recoat 3 - 4 Hours

THEORETICAL A guide to the theoretical coverage which can be achieved under normal

COVERAGE conditions is 4-6m²/liter /coat.

APPLICATION: Putty applicator

THINNING Ready to Use

CLEANING UP Clean all equipment with water immediately after use.

SURFACE PREPARATION

New or bare surfaces must be clean, dry and free from efflorescent salts.

Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or stiff brushes and dust off. Treat any area affected by mold, lichens, algae or moss with bleach. After priming new surfaces with Primax Power Primer, fill the surface with Primax Power Wall Putty. Allow the filler to dry for 2-3 hrs and apply second coat of Primax Power Wall Putty. Primax Power Wall Putty water based can also be applied directly on new unpainted surfaces. Primax Power Wall Putty water based is not recommended for exterior use. After surface preparation apply 2-3 coats of Primax Power Decorative paint.



PRIMAXTM
PAINTS

FLASH POINT

N/A

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose off paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



PRIMAXTM
PAINTS