

# PRIMAX<sup>®</sup> POWER WATER PRIMER SEALER

Primax Power Water Sealer is a water-based Sealer that protects against alkali and moisture. It is a breathable primer that allows water vapors to evaporate. It is a top-quality primer for use on masonry surfaces including concrete, brickwork, plaster, cement, wall boards, etc.

**PACK SIZE:** 4L 16L

**COLOR RANGE:** White only

**COMPOSITION (NOMINAL):**

Pigment: Lightfast Pigments

Binder: Acrylic Copolymer

Solvent: Water

**FLASH POINT:** N/A

**DRYING TIME:**

Depends on temperature, humidity, air movements, and film thickness

Touch dry: 2-3 Hours

Recoat: 6-8 Hours

**THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 12-14 m<sup>2</sup>/liter/coat.

**APPLICATION:** Brush Roller Spray

**THINNING:**

Brush or Roller: 10-25%

Conventional spray: 30-40%

**CLEANING UP:**

Clean all equipment with water immediately after use.

**SURFACE PREPARATION:**

New, bare, old, or previously painted surfaces must be clean dry, and free from wax and dust. Clean the surface by rubbing it down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust it off with the help of a cloth. Stir the paint thoroughly before use.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION:**

Keep the container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. A cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from the skin, use soap and water or a recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO<sub>2</sub> fire extinguisher. Keep away from the source of ignition. Close the container tightly after each use. Keep out of reach of children. In case of an accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance, or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.

