

# REGAL<sup>®</sup> WALL PUTTY

**GENERAL DESCRIPTION** Primax Regal Wall Putty is a high quality ready to use filler for all types of interior masonry surfaces such as brickwork, plaster, and cement rendering

**PACK SIZE** 1.5 kg, 5 kg, 20 kg

**COLOUR RANGE** White Only

**COMPOSITION (NOMINAL)** Pigment: Inert Fillers  
Binder: PVA Copolymer Emulsion.  
Solvent: Water

**DRYING TIMES** Depends on temperature, humidity, air movements, and film thickness.

Touch dry 2 - 3 Hours

Recoat 3 - 4 Hours

**THEORETICAL** A guide to the theoretical coverage which can be achieved under normal

**COVERAGE** conditions are 4-6m<sup>2</sup> /liter /coat.

**APPLICATION:** Putty applicator

**THINNING** Ready to Use

**CLEANING UP** Clean all equipment with water immediately after use.

## SURFACE PREPARATION

New or bare surfaces must be clean, dry, and free from efflorescent salts.

Remove all defective or poorly adhering material by rubbing down using suitable abrasive paper or stiff brushes and dusting off. Treat any area affected by mold, lichen, algae or moss with bleach. After priming new surfaces with Primax Regal Primer, fill the surface with Primax Regal Smooth Wall Putty. Allow the filler to dry for 2-3 hrs. And apply a second coat of Primax Regal Smooth Wall Putty. Primax Regal Smooth Wall Putty water-based can also be applied directly on new unpainted surfaces. Primax Regal Smooth Wall Putty water-based is not recommended for exterior use. After surface preparation apply 2-3 coats of Primax Regal Decorative paint.

**FLASH POINT** N/A



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION**

Keep the container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. A cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from the skin, use soap and water or a recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO<sub>2</sub> fire extinguisher. Keep away from the source of ignition. Close the container tightly after each use. Keep out of reach of children. In case of an accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance, or service provided by Progressive Paint Industries in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.



**PRIMAX**<sup>TM</sup>  
**PAINTS**