

PRIMAX™ WOOD CARE SANDING SEALER

Primax Wood Care Sanding Sealer is a nitrocellulose based sanding sealer clear base coat, for all kinds of wood applications such as furniture, chairs, frames of wood, hardwood, plywood, furniture, timberwork such as doors, windows, tables, and cupboards, etc. It protects the top coat by sealing the base of the pour without hiding the wood grains.

PACK SIZE: 0.91 L 3.64 L

COLOR RANGE: Clear

COMPOSITION (NOMINAL):

Pigment: Inert filler

Binder: Nitrocellulose, Alkyd

Solvent: Volatile solvents BA, IPA, XYLENE

FLASHPOINT:

20°C

DRYING TIME:

Depends on temperature, humidity, air movements, and film thickness

Touch Dry for 15 - 20 Minutes

Recoat 1- 1 1/2 Hours

APPLICATION:

Spray

THINNING:

Conventional spray: 50 - 60% with Primax Wood Care thinner

CLEANING UP:

Clean all equipment with Primax Wood Care Thinner immediately after use.

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 13 m² /liter /coat.



PRIMAXTM
PAINTS

SURFACE PREPARATION:

Before application, the surface should be clean, dry, and free from oil, grease, dust, wax, etc. Rub down the surfaces with the help of abrasive paper surface must be scuffed in the direction of grains. Clean with the help of a clean cloth. Apply 1-2 coats of Primax Wood Care Sanding Sealer. Allow it to dry. Slightly rub down the surface with the help of abrasive paper after each coat. Clean with the help of a clean cloth. Apply 2-3 coats of Primax Wood Care Gloss/Matt Lacquer as a top coat. Stir the product thoroughly before use.

SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep the container tightly closed, upright, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter, etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink, and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, mask, and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to the eyes, skin, and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse your mouth with plenty of water (only if the person is unconscious) and show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO₂ fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated places. Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation

