

# PRIMAX™ WOOD CARE THINNER

Primax Wood Care Thinner is a high-quality thinner for multi purposes. It can dissolve almost all types of general paints like N/C Synthetic, C/R, Epoxy, etc. It is mostly used for thinning the paints which are applied with the gun.

**PACK SIZE:** 0.91, L 3.64 L

**COLOR RANGE:** Clear

## **COMPOSITION (NOMINAL):**

Pigment: N/A

Binder: N/A

Solvent: Volatile solvents BA, IPA, XYLENE

**FLASHPOINT:** 29°C

## **DRYING TIME:**

Depends on temperature, humidity, air movements, and film thickness

Touch Dry: N/A

Recoat: N/A

## **APPLICATION:**

Spray

## **THINNING:**

Thinning can be done with Primax Wood Care thinner in Primax Wood Care N.C Clear Gloss Lacquer, Primax Wood Care N.C Matt Lacquer & Primax Wood Care Sanding Sealer.

## **CLEANING UP:**

Clean all equipment with Primax Wood Care Thinner immediately after using NC Products.

## **THEORETICAL COVERAGE:**

N/A

## **SURFACE PREPARATION:**

This Thinner can be used in Primax Wood Care N.C Products.



**PRIMAX**<sup>TM</sup>  
**PAINTS**

## **SAFETY, HEALTH, AND ENVIRONMENTAL INFORMATION**

Highly inflammable. Keep the container tightly closed, upright, and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter, etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink, and animal feeding stuff. Keep the container tightly closed. Wear suitable gloves, masks, and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to the eyes, skin, and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse your mouth with plenty of water (only if the person is unconscious) and show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measures against static charges. Use only in well ventilated places. Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation



**PRIMAX**<sup>TM</sup>  
**PAINTS**